

Grommet Sizes

		B10200XX						B10220XX										
		Sm White OVAL # 24	Sm Orange OVAL # 25	Sm Yellow # 21	Sm White # 20	Sm Red # 16	Sm Blue # 18	Lg White # 91	Lg Yellow # 90	Lg Black # 89	Lg Blue # 88	Lg Gray # 87	Lg Red # 86	Lg Orange # 85				
MAX CORD DIA. (inch)		OVAL (UF) .160 x .360	OVAL (UF) .230 x .440	0.370	0.450	0.560	0.610	0.450	0.560	0.630	0.690	0.750	0.830	0.900				
	Plug	Connector		Yellow	White*	Red	Blue	White*	Yellow	Black	Blue	Gray	Red	Orange	3	4	3Ø	
1510	1610	✓ Optional **	✓ Optional **	✓	✓	✓	✓							X				
1512	1612			✓	✓	✓	✓									X		
1514	1614			✓	✓	✓	✓									X		
1516	1616			✓	✓	✓	✓									X		
1520	1620			✓	✓	✓	✓									X		
1522	1622			✓	✓	✓	✓									X		
1524	1624			✓	✓	✓	✓									X		
2310	2410								✓	✓	✓	✓				X		
2312	2412						✓	✓	✓	✓				X				
2314	2414						✓	✓	✓	✓				X				
2316	2416						✓	✓	✓	✓				X		X		
2317	2417						✓	✓	✓	✓				X				
2320	2420							✓	✓	✓	✓				X			
2322	2422							✓	✓	✓	✓				X	X		
2324	2424							✓	✓	✓	✓				X	X		
2510	2610						✓	✓	✓	✓				X				
2512	2612						✓	✓	✓	✓				X				
2514	2614						✓	✓	✓	✓				X				
2516	2616						✓	✓	✓	✓				X		X		
2520	2620										✓	✓	✓		X			
2522	2622										✓	✓	✓		X	X		
2524	2624										✓	✓	✓		X	X		
2526	2626										✓	✓	✓		X	X		
2528	2628										✓	✓	✓		X	X		
2530	2630										✓	✓	✓		X	X		

* May also appear as light tan

** May be ordered separately - Call Ericson for details

✓ = Included in package

Diameter Ranges of Portable Electrical Cord In Accordance with UL 62

Type	AWG Size	2 Conductors	3 Conductors	4 Conductors
SJ, SJE, SJOO, SJO, SJEO, SJT, SJTO, SJTOO	18	0.280-0.315	0.300-0.335	0.325-0.365
	16	0.305-0.340	0.325-0.360	0.350-0.395
	14	0.335-0.375	0.360-0.395	0.390-0.435
	12	0.405-0.455	0.425-0.475	0.465-0.520
	10	0.540-0.605	0.565-0.635	0.625-0.700
S, SE, SOO, SO, SEO, ST, STOO, STO	18	0.340-0.385	0.360-0.400	0.385-0.430
	16	0.365-0.410	0.385-0.430	0.410-0.460
	14	0.495-0.550	0.520-0.575	0.560-0.620
	12	0.565-0.625	0.590-0.655	0.640-0.710
	10	0.615-0.685	0.650-0.720	0.700-0.775
	8	0.780-0.880	0.830-0.930	0.925-1.050
	6	0.920-1.050	0.970-1.100	1.050-1.200
4	1.060-1.210	1.130-1.280	1.250-1.450	
2	1.210-1.400	1.300-1.500	1.450-1.650	

