

# HÜPER OPTIK™



## CERAMIC 60

## C60

### SPECIFICATIONS

	Single Pane	Double Pane
Visible Light Transmission	60%	58%
Visible Light Reflectance	9%	11%
Shading Coefficient	0.65	0.72
Solar Heat Gain Coefficient	0.57	0.63
Infrared Rejection	60%	60%
UV Light Rejection	99%	99%
Total Solar Energy Rejected	43%	37%
Glare Reduction	34%	36%
U-value	1.04	0.49



HUPEROPTIKUSA.COM

### HÜPER OPTIK™

#### FEATURES

- World's first patented nano-ceramic technology
- Superb durability - resistance to seashore (high-salt) environment
- High total solar energy rejection
- Reduces demetallization or discoloration
- High ultraviolet rejection - greater than 99%
- 100% dye-free and 100% metal-free
- Natural tone with low reflectivity
- Scratch-resistant hardcoat

#### BENEFITS:

- Residential limited lifetime & commercial fifteen-year limited product warranty
- Cutting-edge technology with remarkable heat rejection performance
- Increases comfort - cooler interior
- Reduces glare and fading of interior upholstery
- Saves energy by reducing electricity consumption
- Protects against sun-related skin problems - SPF>200
- Enhances safety with improved glass shatter resistance
- Enhances overall aesthetics with a soft natural tone that is virtually clear

FHSPE-C60



Powered by  
**Meister  
Keramische  
Technologie**

