



You must read and understand this manual before using this firearm.

You must follow all safety precautions and instructions.

If you do not understand any part of this manual or you are unsure about the operation of your firearm, contact Stag Arms before proceeding. If your firearm is not working properly, do NOT return to the store, but contact Stag Arms directly.

STAG ARMS
7052 COMMERCE CIRCLE
SUITE 210
CHEYENNE, WY 82007
307.269.0061
WWW.STAGARMS.COM

A WARNING

Risk of serious injury or death.

Failure to read this manual and to follow the instructions may result in serious injury or death to you or to others.

Be sure you understand all instructions and hazards associated with firearms before using this firearm.

Safety	
Safety Alert Symbol And Signal Words	3
Safety Is Critical To Performance	3
Safety Guidelines	4
Identification	8
Model And Serial Number	8
Part Identification	8
Inspect For Ammunition	9
Ammunition	12
Loading	14
Firing	17
Malfunctions	
Unloading	
Disassembly For Cleaning	26
Remove Bolt Carrier	26
Disassemble Bolt	29
Assemble Bolt	
Remove Buffer And Action Spring	31
Install Buffer And Action Spring	31
Install Bolt Carrier	32
Remove Handguards	
Cleaning	
Cleaning The Barrel	
Cleaning The Chamber	
Cleaning The Exterior	36
Collapsible Buttstock	37
Definition of Terms	38
Limited Warranty	40
Service	42
Customer Service	42
D :	40

SAFETY

SAFETY ALERT SYMBOL AND SIGNAL WORDS

This manual provides instructions on the operation and maintenance of rifles made by Stag Arms. You must read, understand and follow the instructions and safety warnings in this manual. The safety of yourself and those around you, depends on the knowledge you have of your rifle, and your knowledge of the safety guidelines common to all firearms.

The safety information in this manual is denoted by the safety alert symbol:

The level of risk is indicated by the following signal words.

A DANGER

Indicates a hazardous situation, which, if not avoided, will result in death or serious injury.

WARNING

Indicates a hazardous situation, which, if not avoided, could result in death or serious injury.

A CAUTION

Indicates a hazardous situation, which, if not avoided, could result in minor or moderate injury.

NOTICE

Indicates a situation that could result in damage to the equipment or other property.

SAFETY IS CRITICAL TO PERFORMANCE

A well crafted gun is only as good as the hands that hold it. Shooting accidents are often caused by careless oversights. These oversights can result in the loss of life, limb or property. Proper use and performance of your firearm depends on correct assembly and maintenance, which is why it is critical you read and understand the information in this www.stagarms.com

manual. Use the following safety guidelines in every situation.

SAFETY GUIDELINES

WARNING

You must follow all of the safety guidelines to ensure the safe use of your firearm. Failure to follow these basic firearm safety quidelines may result in an unintended discharge which could cause serious injury or death.



Treat every firearm as if it's loaded.

A dropped firearm may discharge. Do not drop your firearm.

Always keep your firearm pointed in a safe direction. Never point a firearm at anyone whether the firearm is loaded or not. Be careful when you're loading or unloading your firearm.

Firearms must be unloaded when not in use.

Load your firearm only when you are in the field or target range and ready to fire. Never let a loaded firearm out of your sight. Completely unload your firearm as soon as you are finished shooting, before storing, traveling, standing it against anything, laying it down, entering a vehicle, entering a building or bringing it into your home. Do not take anyone's word that a firearm is unloaded, always verify for yourself. Never pass your firearm to another person until you visually check that it is unloaded. Keep vour firearm unloaded and safely stored when not in use.

Never rely on your firearm mechanical features alone. Only your safe handling of your firearm, will ensure the safe use of your firearm. A mechanical safety is not a substitute for common sense. It is merely a supplement to your safe handling of a firearm. Never touch the trigger or trigger guard until you are ready to fire. Be sure that no other objects touch the trigger. Never climb a tree or cross obstacles such as streams, creeks, or fences with a loaded firearm.

Verify the barrel is clear of obstructions before loading and firing. Completely unload the firearm and check the barrel for any obstructions or debris. Never let water, snow, mud or other materials enter the barrel. Excess lubricants or grease can dangerously increase pressure and may cause barrel to burst when firing. If barrel is obstructed, remove ammunition and clean barrel immediately.

Every firearm is designed to use a certain gauge or caliber of ammunition. Never use the wrong ammunition, or non-standard, or "handloaded" ammunition which has not been subjected to internal ballistic pressure testing. Always read and follow the instructions on the ammunition box.

Be sure of your target and the surrounding area. Never fire unless you know exactly where your shot is going, and what it will strike. Make sure the shot has a safe back stop, such as a hillside or sand. Bullets can ricochet on surfaces such as water. Do not fire into the sky.

A Safely store and secure your firearm and ammunition separately. Store your firearm and ammunition so that they are not accessible to children or unauthorized persons. Evaluate your personal situation to be sure children and unauthorized persons cannot access your firearm.

You are responsible for your firearm at all times. You must protect yourself and others against injury or death from misuse of a firearm.

A Never lock a loaded firearm and never load a locked firearm.

Always wear appropriate eye and ear protection while shooting and cleaning a firearm. Be sure others in the vicinity have protection as well.

A Never use drugs or alcohol before or during use of firearm. Never use your firearm if you are taking

any medication which impairs, even slightly, your mental or physical ability.

⚠ Obey all laws regarding the storage, security, transportation and carrying of firearms.

You must be familiar with all local, state, and federal laws regarding the safe use, storage and/or transportation of your firearm. Your local police department can answer any questions you may have regarding the legal use, storing and/or transporting of your firearm.

Discharging firearms in poorly ventilated areas, cleaning the firearm, and the handling of ammunition may result in exposure to lead and other substances known to cause birth defects, reproductive harm, cancer, and other physical injury. Wash hands thoroughly after exposure. Read the warnings and labels on all ammunition and cleaning products carefully.

Understand all operational aspects of the firearm before handling. Every firearm is different. Familiarize yourself with all mechanical features of your firearm. If you do not understand any part of this manual or you are unsure about the operation of your firearm, contact Stag Arms at 1-860-229-9994 before proceeding.

If your firearm fails to fire when the trigger is pulled, handle with care. Keep the firearm pointed in a safe direction. Keeping your face away from the breach, put the safety on. Unload your firearm and dispose of the ammunition safely.

Never alter or modify your firearm. Never disassemble your firearm beyond what is outlined in this manual. Improper manipulation of any internal components and/or improper disassembly or reassembly may be dangerous, and may lead to serious injury or death. Do not try to change your firearm's trigger pull, alterations might cause accidental firing. Only a qualified gunsmith should service, repair, or modify your firearm in any way.

Be sure all accessories are compatible with your firearm. Accessories must not interfere with the safe operation of your firearm.

Never allow your firearm to be used by an individual who does not understand its safe operation or has not read these firearm safety guidelines.

The safe use of your firearm is your personal responsibility. Failure to follow all of these basic safety guidelines may result in severe injury or death to you or others.

You, the owner, are the most important safety device when it comes to the use of your Stag Arms Firearm.

Under no circumstances will Stag Arms be responsible for any injury, death or property damage that results from:


- A disregard of the safety guidelines and warnings;
- The criminal or negligent use of the firearm;
- Improper or careless handling of the firearm;
- Improper or negligent modifications or repairs to the firearm;
- The use of non-standard, defective, improper or reloaded ammunition.

This manual must accompany this firearm and be transferred with it upon change of ownership or when presented to another person.


IDENTIFICATION

MODEL & SERIAL NUMBER

The serial number (A) and model (B) are located on the left side of the firearm. See figure 1.



PARTS IDENTIFICATION



A - Muzzle

Device

B - Hand Guard

C - Upper Receiver

D - Bolt Catch

E - Charging Handle

F - Stock

G - Safety Lever

H - Grip

I - Trigger

J - Trigger Guard

L - Bolt Assist

M - Magazine

Release

Button

N - Dust Cover

The rifle shown in the photos of this manual is our Right-Handed Stag 15 Tactical, and may vary from the model you purchased.

INSPECT FOR AMMUNITION

WARNING

Risk of serious injury or death.

A loaded firearm may discharge unintentionally.

Point the firearm in a safe direction while inspecting for ammunition.

1. Place the safety selector lever (A) on SAFE. See figure 2.



Figure 2

2. Grasp the firearm while keeping your finger off the trigger. Press the magazine release button (B) and pull the magazine (C) down to remove. See figure 3.



Figure 3

3. Unlock and pull the charging handle (D) all the way out and press in on the lower portion of the bolt catch (E). Release charging handle. This locks the bolt in the open position. See figure 4 and 5.



Figure 4



Figure 5

4. Look into the receiver through the ejection port and verify that there are no cartridges in the chamber (F). See figure 6.



Figure 6

5. Follow this inspection procedure before storage, cleaning, transporting and before handing to another person or when handed to you.

AMMUNITION

DANGER

Risk of serious injury or death.

Failure to use the proper gauge or caliber of ammunition will cause your firearm to fail when firina.

Always use ammunition specifically designed for use in your firearm.

You are responsible for using ammunition specifically designed for and that meets industry standards for use in your firearm.

Using ammunition not specifically designed for your firearm can cause the pressure to exceed the capability of your firearm, and could damage and/or rupture your firearm.



Never mix ammunition.

Locate the caliber mark (A) on the firearm's See figure 7. This designates ammunition caliber that must be used in your firearm.



Figure 7

Always inspect your ammunition before it. Never use damaged or corroded ammunition which could lead to a burst cartridge causing damage to the firearm and possible personal injury or death.

Always use ammunition that is commercially manufactured with internal ballistic pressures which are in strict accordance with the specifications of the Sporting Arms and Ammunitions Manufacturers' Institute (SAAMI). For verification, contact your ammunition supplier.

Your firearm has been designed for ammunition of a specific caliber and type. The firearm and ammunition work together as a system. You must use the correct ammunition for your firearm.

A WARNING

Risk of serious injury or death.

Use of "handloaded", reloaded or non-standard ammunition may cause your firearm to fail to fire, jam, or to dangerously increase pressure and cause barrel to burst when firing.

Use only quality commercially manufactured ammunition.

LOADING

A WARNING

Risk of serious injury or death.

A loaded firearm may discharge unintentionally if dropped.

Handle the loaded firearm with care.

Clean your firearm before the first use. Your firearm has been treated at the factory to prevent corrosion. The chamber, bore, and exterior surfaces must be cleaned to remove excess oil.

A You must read and understand this manual before loading.

Load your firearm only when you are in the field or target range, when you are sure of the target and ready to fire.

- 1. Inspect the firearm for ammunition if you have not done so. See Inspect For Ammunition in this manual.
- 2. Verify that the safety lever is in the SAFE position. For left-handed rifles, the safety lever will be on the opposite side of the rifle.
- 3. Press the upper portion of the bolt catch (A) and the bolt (B) should spring forward. Be sure the bolt is fully forward and locked. See figure 8.



Figure 8 www.stagarms.com

A WARNING

Risk of serious injury or death.

Using damaged, incorrect, non-standard, or "handloaded" ammunition may result in firearm failure or misfire.

Use only quality undamaged ammunition in your firearm.

- 4. Inspect each cartridge for signs of damage. Do not load damaged ammunition. Load the magazine with the proper caliber of undamaged ammunition.
- 5. Push the magazine (C) up into the magazine well until the magazine release button (D) engages and holds the magazine. Use your hand and tap on the bottom of the magazine to be sure it is seated. See figure 9.



Figure 9

▲ WARNING

Risk of serious injury or death.

After performing step 6, the firearm is loaded and will fire if the safety selector is set to FIRE and the trigger is pulled.

Keep the firearm pointed in a safe direction at all times.

MARNING

Risk of serious injury or death.

Never insert a round into the chamber through the ejection port.

Load the chamber by feeding a round from the magazine only.

6. To load a round into the chamber, pull the charging handle (B) fully rearward and release. Tap the forward assist (E) with your hand to be sure the bolt is fully forward and locked. A round from the magazine is now loaded into the chamber. See figure 10.



Figure 10

FIRING

WARNING

You must follow all of the safety guidelines to ensure the safe use of your firearm. Failure to follow these basic firearm safety guidelines may result in an unintended discharge which could cause serious injury or death.

Always point the barrel in a safe direction.

Be alert and follow safety instructions.

Be aware of others. Persons in the vicinity of your shooting may unintentionally walk into your line of fire.

The proper eye and ear protection must be worn by the shooter and bystanders in the area.

1. Grasp the firearm with one hand on the hand guard and the other on the grip. Keep fingers away from the trigger and trigger guard. See figure 11.



Figure 11

Place the buttstock firmly against your shoulder.

3. Move the safety lever to FIRE. See figure 12.



Figure 12

- 4. Aim at the target and gently pull the trigger with your index finger to fire. Release the trigger and the chamber will reload immediately. You may continue to fire by pulling the trigger and fully releasing until the magazine is empty.
- 5. When you stop firing, remove your finger from the trigger and place the safety lever in the SAFE position. See figure 13.



Figure 13

6. Remove and reload magazine if you plan to continue shooting.

▲ WARNING

Risk of serious injury or death.

The firearm may have a round in the chamber even though the magazine has been removed. Keep the firearm pointed in a safe direction while the magazine is reloaded.

7. Unload the firearm using the Inspect For Ammunition procedure in the manual.

19

MALFUNCTIONS

WARNING

Risk of serious injury or death.

If your firearm is not operating properly, stop firing immediately.

Point the firearm in a safe direction and unload the firearm.

Safely store the firearm and take it to a qualified gunsmith for inspection.

A If a cartridge jams or hangs up while moving from the magazine into the chamber, do not attempt to force the cartridge into the chamber.

If your firearm misfires or jams:

1. Remove your finger from the trigger area, point the firearm in a safe direction and wait 10-15 seconds.

2. Place the safety selector lever (A) on SAFE. See figure 14.



Figure 14

3. Press the magazine release button (B) and pull the magazine (C) down to remove. See figure 15.



Figure 15

4. Unlock and pull the charging handle (D) all the way out and press in on the lower portion of the bolt catch (E). Release charging handle. This locks the bolt in the open position. See figure 16 and 17.



Figure 16



Figure 17 www.stagarms.com

5. Look into the receiver and verify that there are no cartridges in the chamber (F). See figure 18.



Figure 18

6. If a cartridge cannot be removed, safely store the firearm and take it to a qualified gunsmith for inspection.

UNLOADING

1. Place the safety selector lever (A) on SAFE. See figure 19.



Figure 19

2. Press the magazine release button (B) and pull the magazine (C) down to remove. See figure 20.



Figure 20

3. Unlock and pull the charging handle (D) all the way out and press in on the lower portion of the bolt catch (E). Release charging handle. This locks the bolt in the open position. See figure 21 and 22.



Figure 21



4. Look into the receiver and verify that there are no cartridges in the chamber (F). See figure 23.



Figure 23

DISASSEMBLY FOR CLEANING

A WARNING

Risk of serious injury or death.

Always point the firearm in a safe direction.

A WARNING

Risk of serious injury or death.

Verify that the firearm is not loaded before any disassembly or cleaning is begun.

WARNING

Risk of serious injury or death.

Do not disassemble the firearm any further than instructed in this manual.

Do not modify or alter any part of the firearm.

Wear the appropriate protective clothing while disassembling and assembling the firearm.

Disassembling the firearm and the handling of ammunition and cleaning products may result in exposure to lead and other substances known to cause birth defects, reproductive harm, cancer, and other physical injury. Wash hands thoroughly after exposure. Read the warnings and labels on all ammunition and cleaning products carefully.

REMOVE BOLT CARRIER

1. Verify that the firearm is not loaded. See Unloading in this manual.

2. Verify that bolt is in the forward position.

3. Push in on the takedown pin (A) from the left side of the firearm. See figure 24.



Figure 24

4. Pull the takedown pin (A) out as far as it will go. The pin will not be removed from the firearm. See figure 25.



Figure 25

5. Pivot the lower receiver away from the upper receiver.

Note: The upper and lower receivers may be separated by removing pivot pin (B). See figure 26.




Figure 26

6. Pull back on the charging handle (C) to remove charging handle and bolt carrier assembly (D). See figure 27 & 28.



Figure 27



7. Clean charging handle and bolt carrier components with a quality gun cleaning solution. Lubricate components with a quality gun lubricant.

WARNING

Risk of serious injury or death.

Do not disassemble the firearm any further than instructed in this manual.

Do not modify or alter any part of the firearm.

Replacement parts must be installed by a qualified gunsmith.

DISASSEMBLE BOLT CARRIER

- 1. Remove bolt carrier assembly from firearm. See Remove Bolt section previously in this manual.
- 2. Remove the firing pin retaining pin (A). Do not distort the ends of the retaining pin. See figure 29.



Figure 29

3. Push the bolt assembly (B) into the bolt carrier to the locked position as illustrated in figure 30.



Figure 30

4. Remove the firing pin (C) through the rear of the bolt carrier assembly. See figure 31.





Figure 31

ASSEMBLE BOLT

1. Insert the firing pin (C) through the rear of the bolt carrier assembly. See figure 32.



2. Pull the bolt out and install the firing pin retaining pin (A). See figure 33.




Figure 33

REMOVE BUFFER AND ACTION SPRING

 Verify that the firearm is not loaded. See Unloading in this manual.

Hold the buffer (A) in and press down on retainer (B) to release buffer.



3. Remove the buffer (A) and spring (C). See figure 34.




Figure 34

▲ WARNING

Risk of serious injury or death.

Do not disassemble the firearm any further than instructed in this manual.

Do not modify or alter any part of the firearm.

Replacement parts must be installed by a qualified gunsmith.

4. Clean buffer and spring components with a quality gun cleaning solution. Lubricate components with a quality gun lubricant.

INSTALL BUFFER ACTION AND SPRING

1. Insert the action spring onto the buffer and into receiver. Press down on retainer (B) and push buffer (A) past retainer, then release retainer. See figure 35.




Figure 35
INSTALL BOLT CARRIER

1. Engage and partially insert charging handle (C). Install bolt carrier (D) so that slot in carrier engages tab on charging handle. Push carrier and charging handle into receiver. See figure 36.



Figure 36

2. Verify the safety selector is on SAFE. See figure 37.



Figure 37

2. Pivot the lower receiver to the upper receiver and push the takedown pin (A) in. See figure 38.



Figure 38

REMOVING HANDGUARD

- 1. Using a hex tool, insert into taper lock wedge with lock symbol (F) and begin unscrewing until the taper lock wedge with lock symbol (F) and turnbuckle screw (H) come loose.
- 2. Slide taper lock wedge with unlock symbol (E) out of dovetail slot.
- 3. Slide handguard off of barrel. See figure 39.

Note: Sometime a wedge may not slide right out, if this occurs, gently tap the opposite side with a nonmarring tool to dislodge it.




Figure 39

INSTALLING HANDGUARD

- 1. Install handguard over barrel nut. Verify handguard is aligned with upper receiver for a smooth transition on each side.
- 2. Insert taper lock wedge (E) with unlock symbol on right side of handguard as shown.
- 3. Insert taper lock wedge with lock symbol (F) over hex tool (G) and into turnbuckle screw (H).
- 4. Insert turnbuckle screw (H) into taper lock wedge (E). Hold equal inward pressure on both taper lock wedges and rotate turnbuckle screw to pull taper lock wedges equally into handguard. Tighten to secure handguard to upper receiver. See figures 40 and 41.




Figure 40



Figure 41

CLEANING

▲ WARNING

Risk of serious injury or death.

Always point the firearm in a safe direction.

WARNING

Risk of serious injury or death.

Verify that the firearm is not loaded before any disassembly or cleaning.

NOTICE

Risk of firearm damage.

Some cleaning solutions and solvents may damage your firearm.

Use a cleaning solution that is designed for use on firearms.

NOTICE

Risk of firearm damage.

Do not allow cleaning rods to scratch the inside of the barrel or chamber.

Commercial firearm cleaning kits are available from your firearms distributor. Follow the instructions included with the cleaning kit.

Clean the firearm before the first use to remove excess oil.

WHEN TO CLEAN

INITIAL CLEANING & LUBRICATION

Your firearm may still have grease and oils from the manufacturing process that are not suitable for proper function. This should be cleaned off each component and a high-quality firearms lubricant generously applied.

BEFORE FIRING

Check that the barrel and chamber are clean and dry.

AFTER FIRING

Clean your firearm as soon as possible so that the job will be easier and there will be less opportunity for corrosion to start. Check it again after a few days to ensure no further cleaning is necessary.

PERIODICALLY

We suggest that you inspect your firearm periodically, depending on your climate, to ensure that it is still serviceable and free of corrosion.

CLEANING THE BARREL

Remove the magazine and verify that the firearm is not loaded and safety is on SAFE.

Clean the chamber with solvent and a chamber cleaning brush specific to your firearm. Move the brush through the chamber several times to scrub the inside of the chamber. Use a clean patch to wipe the chamber after cleaning. Repeat with clean patches until patch stays clean. After cleaning, run a dry patch through the chamber. Do not oil the chamber.

CLEANING THE CHAMBER

Remove the magazine and verify that the firearm is not loaded and safety is on SAFE.

Clean the barrel with a cotton patch attached to a cleaning rod. Moisten the patch with cleaning solution. Repeat with clean patches until patch stays clean. Apply cleaning solvent to a bronze bore brush to help loosen particles inside the barrel. After cleaning, run a dry patch through the barrel and then follow with a lightly oiled patch.

CLEANING THE EXTERIOR

Remove the magazine and verify that the firearm is not loaded and safety is on SAFE.

Wipe all metal surfaces with a clean cloth and then follow up with a lightly oiled cloth.

COLLAPSIBLE BUTTSTOCK

Always point the barrel in a safe direction.

To extend or retract the buttstock, pull lever (A and move buttstock to the desired position. See figure 49.



Figure 49

DEFINITION OF TERMS

<u>Barrel</u> – The tube through which the bullet travels when the firearm is fired.

<u>Bolt</u> – A sliding bar that pushes the cartridge into place and extracts the empty cartridge after firing.

<u>Buttstock</u> – The part of the stock located behind the breech mechanism in a firearm.

<u>Bolt Catch</u> – The lever that, when depressed, releases the bolt carrier assembly to the forward position.

<u>Caliber</u> – The diameter of the bolt, designated in hundredths or thousandths of an inch (.357) or in millimeters (9mm).

<u>Charging Handle</u> – This cocks the firearm when preparing to fire or clean.

<u>Handguard</u> – This is a protective shield that covers the gas tube and the barrel keeping your hand away from the hot barrel.

Firing Pin – A part of the firing mechanism used in a firearm.

<u>Flash Suppressor</u> – This reduces the amount of flash from the muzzle when the weapon is fired.

<u>Magazine</u> – A metal receptacle for a number of cartridges, inserted into certain types of automatic weapons and when empty removed and replaced full receptacle in order to continue firing.

<u>Rifle</u> – A weapon that can be fired from the shoulder.

<u>Safety Selector Lever</u> – This feature changes the trigger between the safe mode and the firing modes.

<u>Sight</u> – A device used to assist aim by guiding the eye.

<u>Trigger</u> – A small projecting tongue in a firearm that, when pressed by the finger, actuates the mechanism that discharges the weapon.

<u>Upper Receiver</u> – The part of the receiver containing the barrel, sights, bolt, and associated parts.

For more detailed information or any other questions you may have, please visit stagarms.com or call our customer service at 307-269-0061.

LIMITED WARRANTY

Complete firearms which ship from the Stag Arms LLC factory are warranted to be free from defects in materials and craftsmanship for the lifetime of the rifle. Parts and accessories are warranted for one year from the date of purchase. The liability of Stag Arms LLC under this warranty shall be limited solely to the obligation to repair or replace the item or defect at its discretion and pay for round trip shipping. The online warranty registration must be completed submitted to Stag Arms LLC through our website at www.stagarms.com/support/customer-service/onlinewarranty.html. This warranty is transferable to future owners. Modification of firearm will void this warranty. This warrantv does cover normal wear or any damage resulting from careless handling, neglect, repairs and adjustments, corrosion or improper ammunition.

Warranty claim, initiate To а call Stag Customer Service at 307.269.0061 Monday Friday 8:00 am - 4:30 pm MST or visit our contact us page at stagarms.com and complete the form, you will then be contacted by our service department. Warranty claims need to state writing) the model and serial number firearm concerned, a description of the difficulty experienced, and include the original receipt with date of purchase.

If your product is not working properly, do not return to the store. For service and technical assistance on this product, call 307-269-0061. Under no circumstances shall Stag Arms LLC be responsible for incidental or consequential damages with respect to economic loss or injury to property, whether as a result of express or implied warranty, negligence or otherwise. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you. Stag Arms LLC will not be responsible for the results of careless handling, unauthorized adjustments, defective, low-quality, reloaded, or improper ammunition, corrosion, neglect, ordinary wear and tear, or unreasonable use.

NOTE: Handguns and long guns are classified as FIREARMS or DANGEROUS WEAPONS. Guns that are surrendered by Stag Arms LLC with the express understanding that it assumes no responsibility for resale handling under local laws and regulations.

NOTE: Lead Exposure: Discharging firearms in poorly ventilated areas, cleaning firearms, or handling ammunition may result in exposure to lead, a substance known to cause birth defects, reproductive harm, and other serious physical injury. Have adequate ventilation at all times. Wash your hands thoroughly after exposure to lead.

NOTE: Stag Arms does not recommend modifying firearms yourself. Any repair or modification needed should only be done by a qualified gunsmith. Always Practice Safe Firearm Procedures.

SERVICE

CUSTOMER SERVICE

At Stag Arms LLC we believe excellence is of the greatest importance. Like our products. our customer service representatives exceed the highest standards of customer support. If you have any questions about the Stag Arms product line, you'll find a helpful member of our team at your service - just call our Customer Service Line at **307.269.0061** Monday – Friday between 8:00 a.m.– 4:30 p.m. MST. We would be happy to also promptly answer your questions or take your order inquiries through at customerservice@stagarms.com.

RETURNS

unused, unopened products may be returned within 30 days. A restocking fee of will be assessed on all purchases over \$100. Returns must be approved ahead of time by calling 307.269.0061 and speaking а customer service representative or to stagarms.com and filling out the manufacturing form. lf а defect or workmanship error is present, contact Arms and at the manufacturer's discretion will be repaired or replaced.

