



# LED DOWNLIGHTS

Direct-to-Ceiling and Surface Mount Downlight Selection Guide









### Why Downlights?

#### **Energy Efficiency**

LEDs are used in a wide range of applications because they use less watts, longer life expectancy, compact size and ease of maintenance.

#### Easy to Install

Each downlight offers its own level of ease. Direct-to-Ceiling (DtC) is as easy as snap and go. Our Horizon and Zeo collections each come with mounting plates, and from there, it's a snap. Low Profile discs have a mounting bracket that twists into place and a retrofit kit that allows it to pop over an existing recessed can.

#### **Placement Flexibility**

Our downlights are slender and ultra accommodating. The DtC line steps up the versatility with a slim profile that hugs the ceiling, with a tethered j-box that makes working around joists and duct work endlessly more flexible.

#### Versatile Style

With a look that's as stunning as its versatility, the sleek, modern profile of our downlight and recessed lights fit in with almost any décor style. Multi-tasking and minimalist, these lights are small enough for a closet, or to line the perimeter of a room and bright enough to fill once-dark corners with light.

### Why Choose Kichler?

#### **Kichler APS Services**

Need help with the placement of a light for the proper effect? Our Advanced Product Solution and Layout (APS) team has you covered.

#### **Kichler Warranty**

Backed by a 5-Year warranty

#### **Complete Lighting Solution**

So much more than just a fixture, we offer a full lighting solution for every room, inside and out.

#### **Order Confidence**

Our downlight comparison chart, plus tips and education, help you choose the right design and light for your project.



#### All Kichler Downlights have a 5-year warranty and offer:


Dimming Capability | Integrated LEDs | Energy Efficiency | Third-Party Validation\*



### Why Kichler Direct-to-Ceiling (DtC)?

From general illumination to accent lighting, our DtC product line features a sleek, ultra-slim profile that's nearly flush to the ceiling, reduces glare and provides a uniform appearance. Equipped with a tethered driver and snap-in clips, our DtC fixtures eliminate the need for a junction box. Just snap-in and go. Providing a beautiful, uniform look that is quick and easy to install.





### Key Considerations When Choosing Downlights

We want to make it as easy as possible for you to find the right downlight for your needs, so we've organized this brochure by the details and features that matter most.
























COMPARISON CHART PAGE 20 | ORDERING INFO PAGE 21 | ACCESSORIES PAGE 22

#### Symbol Guide

#### **FIXTURE ATTRIBUTES**



Damp



Wet



Mounts Ceiling or Wall



Title 24 Compliant

2019 Title 24, Part 6 is a document that contains the California Building Energy Efficiency Standards for Residential and Nonresidential Buildings as regulated by the California Energy Commission. Products marked with this logo and labeled as JA8-2019 or JA8-2019-E have been found to meet the requirements stated in 2019 Title 24, Part 6. For more information, visit www.energy.ca.gov/title24.



**ADA Compliant** 

#### **LIGHT SOURCE**



Dimmable



Integrated LED



Edge-lit Technology



Fixture requires supply wire rated for at least 90° C



**Energy Star** 

#### **Abbreviation Key**

WH - White WHT-Textured White NI - Brushed Nickel

OZ - Olde Bronze® BKT - Textured Black NBR- Natural Brass ACO - Antique Copper

### SLIM

The Direct-to-Ceiling (DtC) Slim LED Downlight uses edge-lit technology to present a glowing, evenly dispersed display of light. True to its name, this ultra-slim profile is a literal snap to install. Just trim a hole and snap it into place and let your room glow with shimmering ambient light.



350 1000





#### Slim Round

### Slim Square

LIGHT OUTPUT	Lumen Options	500 / 700 / 810 / 900	500 / 750		
LIGITI OUTFUT	Color Temperature Options	2700, 3000	2700, 3000		
	Size Options	3" / 4" / 5" / 6"	4" / 6"		
STYLE	Profile Height	0.1" from ceiling	0.1" from ceiling		
	Finish Options	WHT (Optional Trim Rings – BKT, NI, OZ NBR, ACO)	WHT (Optional Trim Rings – BKT, NI)		
INSTALLATION	Installation Type	New Construction or Remodel	New Construction or Remodel		
INSTALLATION	Installation Method	Tethered J-box	Tethered J-box		
	Safety Rating	Wet	Wet		
LOCATION	Recommended Ceiling Height	8' - 9'	8' - 9'		
	Recommended Spaces	Living room / Kitchen / Closet Hallway / Bedroom	Living room / Kitchen / Closet Hallway / Bedroom		

#### PRODUCT FEATURES



#### **ACCESSORIES**

- Rough in Plate
- Goof Ring
- Extension Cables

#### TRIM RING FINISH OPTIONS
















# RECESSED

Get a recessed look with the simplest of installations. No need for a can or separate junction box, this multi-tasker uses spring clips to snap the fixture into place. The trim adds a stunning style to this functional fixture while the recess eliminates some glare for a gorgeous glow.

6" ACTUAL SIZE







**Recessed Round** 

Recessed Square

LIGHT OUTPUT	Lumen Options	700 / 900	700 / 900
	Color Temperature Options	2700, 3000	2700, 3000
	Size Options	4" / 6"	4" / 6"
STYLE	Profile Height	0.16" from ceiling	0.1" from ceiling
	Finish Option	WHT (Optional Trim Rings – BKT, NI)	WHT
INSTALLATION	Installation Type	New Construction or Remodel	New Construction or Remodel
INSTALLATION	Installation Method	Tethered J-box	Tethered J-box
	Safety Rating	Wet	Wet
LOCATION	Recommended Ceiling Height	8' / 9-10'	8' / 9-10'
	Recommended Spaces	Kitchen / Living Room / Dining Bathroom / Offices	Kitchen / Living Room / Dining Bathroom / Offices

W (24) (30)

#### **ACCESSORIES**

- $\bullet \ \mathsf{Rough} \ \mathsf{in} \ \mathsf{Plate}$
- Goof Ring
- Extension Cables

#### TRIM RING FINISH OPTIONS





BKT

PRODUCT FEATURES





550

2700, 3000

2"

0.1" from ceiling

 $\mathsf{WHT}$ 

New Construction or Remodel

Tethered J-box

Wet

8' - 9' or less

Closet / Hallway / Bedroom







#### LIGHTING TIP


For task lighting or in rooms with darker walls, wood, tile, or carpet, install downlights closer together or with higher lumens for a brighter space.



# GIMBAL

Highlight what's important with the Direct-to-Ceiling (DtC) Gimbal LED Downlight. Designed to provide a 360-degree adjustable light source, this low-profile, easy-to-install fixture allows you to create a wall wash or focal accents while highlighting that special piece of wall art or fireplace.

6" ACTUAL SIZE







#### Gimbal

Gimbal Mini

LIGHT OUTPUT	Lumen Options	700 / 900	360	
	Color Temperature Options	2700, 3000	2700, 3000	
	Size Options	4" / 6"	2"	
STYLE	Profile Height	0.21" from ceiling / 0.31" from ceiling	0.18" from ceiling	
	Finish Options	WHT	WHT	
INSTALLATION	Installation Type	New Construction or Remodel	New Construction or Remodel	
INSTALLATION	Installation Method	Tethered J-box	Tethered J-box	
	Safety Rating	Damp	Damp	
LOCATION	Recommended Ceiling Height	8' - 9' or less	8' - 9' or less	
	Recommended Spaces	Select sections of a room: near a fireplace, slanted ceilings, over artwork or focal walls	Select sections of a room: near a fireplace, slanted ceilings, over artwork or focal walls	

#### PRODUCT FEATURES




#### **ACCESSORIES**

- Rough in Plate
- Goof Ring
- Extension Cables

#### ADDITIONAL INFO

• Rotates 360 around with max tilt angle of 30 degrees





Office / Common Area / Living Room


Office / Common Area / Living Room

#### **ADDITIONAL INFO**

• Also available in larger 10" and 13" size options


PRODUCT FEATURES

Recommended Spaces



#### LIGHTING TIP

With edge-lit technology, light is positioned along the side of the diffuser, pointing in, then strategically reflects throughout to present a uniform light distribution across the full diffuser.





# HORIZON

6.5" ACTUAL SIZE

Reach for the stars with Horizon, blending the seamless look of recessed light with the installation ease of a junction-box fixture, the Horizon family of LED downlights is a recessed lighting alternative adored by both end-users and installers.







Horizon

Horizon II

LIGHT OUTPUT	Lumen Options	850	850		
	Color Temperature Options	3000	2700, 3000		
	Size Options	6.5"	6.5"		
STYLE	Profile Height	.5" from ceiling	.75" from ceiling		
	Finish Options	WH	WH		
INICTALLATION	Installation Type	New Construction	New Construction		
INSTALLATION	Installation Method	4" octagon or square j-boxes with 2 1/8" depth	Most standard 4" round, square or octagon j-boxes with 2 1/8" depth		
	Safety Rating	Wet	Wet		
LOCATION	Recommended Ceiling Height	8' - 9'	8' - 9'		
	Recommended Spaces	Kitchen / Living Room / Bedroom	Kitchen / Living Room / Bedroom		


**₩₽₽₽₽** 

#### **ADDITIONAL INFO**

- Horizon II available in 24 count bulk cartons
- Horizon II works well in coastal environments

PRODUCT FEATURES

• Horizon I *not* for coastal environments










### LOW PROFILE

Our original integrated low-profile LED downlights continue to deliver, providing the flush to ceiling look customers want and the installation ease professionals desire.

7.5" ACTUAL SIZE







GENI

**GENII** 

	LIGHT OUTPUT	Lumen Options	850	1000	
	LIGHT OUTPOT	Color Temperature Options	2700, 3000, 4000	2700, 3000, 4000	
		Size Options	7.5"	7.5"	
	STYLE	Profile Height	1.25" from ceiling	1.25" from ceiling	
		Finish Options	WH	WH / NI / OZ	
	INICTAL LATION	Installation Type	New Construction or Remodel	New Construction or Remodel	
	INSTALLATION	Installation Method	All 4" and 3" round, square and octagon J-Boxes, including pancake boxes	All 4" and 3" round, square and octagon J-Boxes, including pancake boxes	
		Safety Rating	Wet	Wet	
	LOCATION	Recommended Ceiling Height	8' - 9'	10' - 12'	
		Recommended Spaces	Closet / Hallway / Bedroom Bathroom	Living room / Kitchen Dining Room / Closet	
PRODUCT FEATURES			<b>WF&amp;</b>	<b>₩₽७७७</b> <u>≈</u> ⊗	

#### **ACCESSORIES**

• Retrofit kit

#### ADDITIONAL INFO

- 24-count bulk packs available
- Not for coastal climates



600

2700, 3000

6"

1.25" from ceiling

WH

New Construction or Remodel


All 4" and 3" round, square and octagon J-Boxes, including pancake boxes

Wet

8' or less

Niches / Reading Nooks / Bay Windows Outdoor Patios / Small Rooms







#### LIGHTING TIP

Ideal downlight placement is 2' away from the wall, and 6' apart from each other to maximize fixture foot candles.



COMPARISON CHART		LIGHT OUTPUT		STYLE		INST	ALLATION	
		Lumen Options	Color Temp Options	Profile Height	Finish Options	Installation Type	Installation Method	
		3"	500			WHT (Optional Trim		
	Slim	4"	700	2700			New Construction or Remodel	Tethered
	Round	5"	810	3000	0.1" from ceiling	Rings – BKT, NI, OZ, NBR, ACO)		J-box
SLIM		6"	900					
	Slim	4"	500	2700	0.1" from ceiling	WHT (Optional Trim	New Construction or	Tethered
	Square	6"	750	3000	o.i from centing	Rings – BKT, NI)	Remodel	J-box
	Recessed	4"	700	2700	0.16" from ceiling	WHT	New	Tethered
	Round	6"	900	3000	0.16 From Celling	(Optional Trim Rings – BKT, NI)	Construction or Remodel	J-box
	Recessed	4"	700	2700	0.18 from poiling	WHT	New Construction or Remodel	Tethered J-box
RECESSED	Square	6"	900	3000	0.1" from ceiling			
	Recessed Mini	2"	550	2700 3000	0.11" from ceiling	WHT	New Construction or Remodel	Tethered J-box
The same of the sa	Gimbal	4"	700	2700	0.21" from ceiling	0.21" from ceiling  WHT	New Construction or	Tethered
		6"	900	3000	0.31" from ceiling	VVIII	Remodel	J-box
GIMBAL	Gimbal Mini	2"	360	2700 3000	0.18" from ceiling	WHT	New Construction or Remodel	Tethered J-box
	Zeo Round	7"	820	3000 4000	1" from ceiling	WH / NI	New Construction or Remodel	All 4" and 3" round, square and octagon J-Boxes, including pancake boxes
ZEO	Zeo Square	7"	820	3000 4000	1" from ceiling	WH / NI	New Construction or Remodel	All 4" and 3" round, square and octagon J-Boxes, including pancake boxes
	Horizon	6.5"	850	3000	0.5" from ceiling	WH	New Construction	4" octagon or square j-boxes with 2 1/8" depth
HORIZON	Horizon II	6.5"	850	2700 3000	0.75" from ceiling	WH	New Construction	Most standard 4" round, square or octagon j-boxes with 2 1/8" depth
LOW PROFILE	GEN I	7.5"	850	2700, 3000 4000	1.25" from ceiling	WH	New Construction or Remodel	All 4" and 3" round, square and octagon J-Boxes, including pancake boxes
	GEN II	7.5"	1000	2700 3000 4000	1.25" from ceiling	WH / NI / OZ	New Construction or Remodel	All 4" and 3" round, square and octagon J-Boxes, including pancake boxes
	Small	6"	600	2700 3000	1.25" from ceiling	WH	New Construction or Remodel	All 4" and 3" round, square and octagon J-Boxes, including pancake boxes

	LOCATIO	N	ORDERING INFORMATION			
Safety Rating	Recommended Ceiling Height	Recommended Spaces	2700 Color Temperature	3000 Color Temperature	4000 Color Temperature	
			DLSL03R2790WHT	DLSL03R3090WHT	-	
		Living room	DLSL04R2790WHT	DLSL04R3090WHT	-	
Wet	8' - 9'	Kitchen / Closet Hallway / Bedroom	DLSL05R2790WHT	DLSL05R3090WHT	-	
			DLSL06R2790WHT	DLSL06R3090WHT	-	
Wet	8' - 9'	Living room Kitchen / Closet	DLSL04S2790WHT	DLSL04S3090WHT	-	
Wet	o s	Hallway / Bedroom	DLSL06S2790WHT	DLSL06S3090WHT	-	
Wet	8' / 9-10'	Kitchen Living Room / Dining	DLRC04R2790WHT	DLRC04R3090WHT	-	
Wet	0,3,6	Bathroom / Offices	DLRC06R2790WHT	DLRC06R3090WHT	-	
Wet	8' / 9-10'	Kitchen Living Room / Dining	DLRC04S2790WHT	DLRC04S3090WHT	-	
Wet	0,3,6	Bathroom / Offices	DLRC06S2790WHT	DLRC06S3090WHT	-	
Wet	8' - 9' or less	Closet Hallway Bedroom	DLMN02R2790WHT	DLMN02R3090WHT	-	
Damp	8' - 9' or less	8' - 9' or less Select sections of a room	DLGM04R2790WHT	DLGM04R3090WHT	-	
Samp			DLGM06R2790WHT	DLGM06R3090WHT	-	
Damp	8' - 9' or less	Select sections of a room	DLMG02R2790WHT	DLMG02R3090WHT	-	
Wet	8' - 9'	Office Common Area Living Room	-	44244WHLED30 44244NILED30	44244WHLED40 44244NILED40	
Wet	8' - 9'	Office Common Area Living Room	-	44245WHLED30 44245NILED30	44245WHLED40 44245NILED40	
Wet	8' - 9'	Kitchen Living Room Bedroom	-	43855WHLED30T	-	
Wet	8' - 9'	Kitchen Living Room Bedroom	43870WHLED27 43870WHLED27B	43870WHLED30 43870WHLED30B	-	
Wet	8' - 9'	Closet / Hallway Bedroom Bathroom	43846WHLED27 43846WHLED27B	43846WHLED30 43846WHLED30B	43846WHLED40	
Wet	10' - 12'	Living room / Kitchen Dining Room /Closet	43848WHLED27T 43848WHLED27TB 43848NILED27T 43848OZLED27T	43848WHLED30T 43848WHLED30TB 43848NILED30T 43848OZLED30T	43848WHLED40T 43848OZLED40T	
Wet	8' or less	Niches / Reading Nooks / Bay Windows Outdoor Patios Small Rooms	43878WHLED27	43878WHLED30	-	

ACCESSORIES		Trim Goof Rings Rings	Rough-In Plate	Extension Cables			Retrofit Kit		
						6'	10'	20'	
	Slim	3"	DLTSL03RBKT DLTSL03RNI	DLGR03WH	DLRP01ST			DLE20WH	
		4"	DLTSL04RACO DLTSL04RBKT DLTSL04RNBR DLTSL04RNI DLTSL04ROZ	DLGR05WH	DLRP02ST	DIFOCHIL			_
	Round	5"	DLTSL05RBKT DLTSL05RNI	DLGR06AWH	DLRP02ST	DLE06WH	DLE10WH		
SLIM		6"	DLTSL06RACO DLTSL06RBKT DLTSL06RNBR DLTSL06RNI DLTSL06ROZ	DLGR07WH	DLRP02ST				
	Slim	4"	DLTSL04SBKT DLTSL04SNI	-	DLRP02ST			DLE20WH	
	Square	6"	DLTSL06SBKT DLTSL06SNI	-	DLRP02ST	DLE06WH	DLE10WH		-
	Recessed Round	4"	DLTRC04RBKT DLTRC04RNI	DLGR05WH	DLRP02ST	DLE06WH	DLE10WH	DLE20WH	_
		6"	DLTRC06RBKT DLTRC06RNI	DLGR06BWH	DLRP02ST				
RECESSED	Recessed Square	4"	-	-	DLRP02ST	DLE06WH	DLE10WH	DLE20WH	-
		6"	-	-	DLRP02ST				
	Recessed Mini	2"	-	DLGR02WH	DLRP01ST	DLE06WH	DLE10WH	DLE20WH	-
	Gimbal	4"	-	DLGR05WH	DLRP02ST	DLE06WH	DLE10WH		
GIMBAL		6"	-	DLGR07WH	DLRP02ST	BEEGGWII	BELIOWIT	DLE20WH	
	Gimbal Mini	2"	-	DLGR01WH	DLRP01ST	DLE06WH	DLE10WH	DLE20WH	-
LOW PROFILE	GEN I	7.5"	-	-	-	-	-	-	4146LED
	GEN II	7.5"	-	-	-	-	-	-	4146LED
	Small	6"	-	-	-	-	-	-	4145LED





# Total Project Solution

From the curb to the mudroom cubby - we offer a lighting solution for your whole home. No need to look anywhere else for your landscape, ceiling fans, or other lighting needs - we can assist you from the inside out.







# Committed to Your Project Success

Whether you are just planning or would like help troubleshooting an installation, our APS team is here to help you every step of the way. For placement and recommendations contact our product solution team at 844-524-4537 or at techsupport@Kichler.com.

Learn more about Kichler Downlights at Kichler.com/downlights

