

## SAS Super 100/180

### The portable microbial air sampler for cleanroom monitoring

The SAS range has been at the fore front of environmental monitoring for over 30 years. The distinctive yellow samplers are used by many of the world's leading pharmaceutical companies to demonstrate GMP compliance within their manufacturing facilities.

Designed and developed in Italy, the SAS Super range of portable microbial air samplers offer the user an easy to use, robust sampler for viable particle monitoring. Typical applications include monitoring within controlled spaces, such as clean rooms, operating theatres or laboratories, as well as office and outdoor environments.

The battery powered units will sample over 40,000 litres on a full charge and are easy to wipe down and clean. Each sampler is supplied complete with carry case, charger and calibration certificate.

### Applications

The SAS portable sampler can be used for many environmental monitoring applications, the key uses are:

- Routine clean room monitoring
- Grade A monitoring of Isolator cabinets
- Operating theatres
- Offices and HVAC systems
- External composting sites
- Investigative work

### Features & benefits

#### Multi-point impaction sampling

Developed from multi stage sieve samplers, the SAS utilizes the proven multi-point impaction method to collect airborne particles. 219 holes of 1mm diameter direct air flow on to the agar surface of a standard plate.

#### Battery powered

The nickel metal hydride battery pack will provide well over 40,000 litres worth of sampling on a single charge. The rapid charger will have the unit fully recharged in 4 hours, allowing significant numbers of samples to be completed per day.



#### Stainless steel sampling head

The 316 stainless steel Drilled Head can be steam autoclaved between uses or decontaminated using proprietary disinfectants or alcohol. Additional heads can be purchased so ensuring a ready to go head is always available.

#### Delay start

The SAS Super has a selectable delay start of 1 - 20 minutes. This allows the user to program the sampler and exit the room being monitored before the sample is taken. A true at rest sample is taken avoiding any impact from the operator.

#### Multi-mode sampling

If a prolonged sample to mimic a process is required, the SAS Super's Multi mode facility is ideal. A standard 1 cubic metre sample can be divided into smaller samples with a time delay between each.

#### Last sample memorised

The SAS Super makes it easy to repeat the same sample as it memorises the last sample set. Simply switch on and press Start to repeat the same sample volume.

# Technical data

Product specifications	
Sampling rate:	SAS Super 100 – 100 litres/minute SAS Super 180 – 180 litres/minute
Sample size:	1 – 1800 litres operator selectable – 8 presets plus 8 user definable
One m <sup>3</sup> run time:	100L version = 10 mins, 180L version = 5mins, 33 secs
Construction materials:	Powder coated polyurethane resin, aluminium & stainless steel ( <i>full details available</i> )
Consumables used:	Contact plates or 90mm Petri dishes – <i>must be defined at ordering</i>
Power supply:	8.4 VDC nickel metal hydride battery pack
Battery capacity:	2450mAh (approx. 40,000 litres of air sampling)
Battery recharge time:	Approx. 4 hours
Sampler dimensions (mm):	304 x 104 x 110 (L x W x H)
Sampler weight (kg):	With Aluminium drilled head – 1.8kg With stainless steel drilled head – 2.0kg
Carry case dimensions (mm):	455 x 368 x 166 (L x W x H)
Total weight (inc sampler, case, charger) kg	With Aluminium drilled head – 4.9kg With stainless steel drilled head – 5.1kg

Ordering information		
Part Number	Description	Packaging
5C0900	SAS Super 100 air sampler, Contact, aluminium Drilled head	Per item
5C0901	SAS Super 100 air sampler, Contact, s/s Drilled head	Per item
5C0950	SAS Super 180 air sampler, Contact, aluminium Drilled head	Per item
5C0951	SAS Super 180 air sampler, Contact, s/s Drilled head	Per item
Optional Extras		
5C1022	Basic Tripod – 1.44m high	each
422000	SAS Stand – stainless steel	each
5C0982	Daily Heads - Contact	Case of 40
5C0983	Daily Heads – 90mm Petri	Case of 40

## Terms & conditions

All SAS air samplers are supplied as complete kits, ready to use, including calibration certificate and a 24 months return to base warranty.

We reserve the right to amend specifications without notice. E&OE



**Telephone:**  
+44 (0)1869 355500



**Email:**  
sales@cherwell-labs.co.uk



**Registered Office:**  
7 & 8 Launton Business Centre,  
Murdock Road,  
Bicester,  
OX26 4XB



**Fax:**  
+44 (0)1869 355545



**Website:**  
www.cherwell-labs.co.uk