

```

<html>
<head>
<title>Company Name</title>
</head>
<body bgcolor="white" text="black" topmargin="0">
<hr />
<center>
<h3>BIM-GSS IMOD IPSERVER BROWSER INTERFACE FORM</h3>
<hr />
<form method="POST" action="HTTP://xxx.xxx.xxx.xxx:yyyy/BIM$CGIC">
<input type="HIDDEN" name="IMOD" value="BIMTCPIM">
IMOD1: <input type="TEXT" name="IMOD1" value=""><br /><br />
TEST1: <input type="TEXT" name="TEST1" value=""><br />
TEST2: <input type="TEXT" name="TEST2" value=""><br />
TEST3: <input type="TEXT" name="TEST3" value=""><br />
TEST4: <input type="TEXT" name="TEST4" value=""><br />
TEST5: <input type="TEXT" name="TEST5" value=""><br />

<input type="submit" value="Start" >
</form>
</center>
</body>
</html>

```

note: In order to use this interface you must be running DATA21's IPSERVER browser and either BSI's or CSI's TCP/IP stack on the VSE machine you wish to access IMODs through. You must define the phase, BIM\$CGIC, to CICS as a program, language ASSEMBLER, execkey of CICS, and to use ANY storage.

You must also be running the BIM-GSS phase, BIM\$CGRX, in a partition on the VSE machine. Please see the BIM\$CGRX text file for more information.

The following variable shown above must be used and is described as follows:

IMOD - Name of the IMOD to be executed. For IMOD execution, this must be BIMTCPIM. For other uses the IMOD must contain up to 8 alphanumeric characters only.

You must make sure that IMOD is the first variable and should remain hidden. IMOD1 needs to contain the name of the actual IMOD you wish to execute. TEST1 through TEST5 are just for demonstration purposes.