

```

<html>
<head>
<title>Company Name</title>
</head>
<body bgcolor="white" text="black" topmargin="0">
<hr />
<center>
<h3>BIM-GSS IMOD TCP/IP for VSE Browser Interface Form</h3>
<hr />
<form method="POST" action="HTTP://xxx.xxx.xxx.xxx:yyyy/BIM$CGIP">
<input type="HIDDEN" name="IMOD" value="BIMTCPIM">
IMOD1: <input type="TEXT" name="IMOD1" value=""><br /><br />
TEST1: <input type="TEXT" name="TEST1" value=""><br />
TEST2: <input type="TEXT" name="TEST2" value=""><br />
TEST3: <input type="TEXT" name="TEST3" value=""><br />
TEST4: <input type="TEXT" name="TEST4" value=""><br />
TEST5: <input type="TEXT" name="TEST5" value=""><br />

<input type="submit" value="Start" >
</form>
</center>
</body>
</html>

```

note: In order to use this interface you must be running CSI's TCP/IP for VSE HTTP daemon and the TCP/IP for VSE stack on the VSE machine you wish to have access to IMODS through. You must add the following entry to the IPINITnn.L member:

```

DEFINE CGI,PUBLIC='BIM$CGIP',TYPE=CGI-BAL,FORMAT=NO
DEFINE USER,ID=$WEB,PASSWORD=$WEB,WEB=YES

```

You must also be running the BIM-GSS phase, BIM\$CGRX, in a partition on the VSE machine. Please see the BIM\$CGRX text file for more information.

The following variable shown above must be used and is described as follows:

```

IMOD      -      Name of the IMOD to be executed.  For
                IMOD execution, this must be BIMTCPIM.  For
                other uses the IMOD must contain up to 8
                alphanumeric characters only.

```

You must make sure that IMOD is the first variable and should remain hidden. IMOD1 needs to contain the name of the actual IMOD you wish to execute. TEST1 through TEST5 are just for demonstration purposes.