

```
<html>
<head>
<title>Company Name</title>
</head>
<body bgcolor="white" text="black" topmargin="0">
<hr />
<center>
<h3>BIM-GSS REXX IMOD IPSERVER BROWSER INTERFACE FORM</h3>
<hr />
<form method="POST" action="HTTP://xxx.xxx.xxx.xxx:yyyy/BIM$CGIC">
<input type="HIDDEN" name="IMOD" value="BIMTCPRX">
IMOD to run: <input type="TEXT" name="IMOD" value=""><br /><br />
<input type="submit" value="Start" >
</form>
</center>
</body>
</html>
```

note: In order to use this interface you must be running DATA21's IPSERVER browser and either BSI's or CSI's TCP/IP stack on the VSE machine you wish to access IMODs through. You must define the phase, BIM\$CGIC, to CICS as a program, language ASSEMBLER, execkey of CICS, and to use ANY storage.

You must also be running the BIM-GSS phase, BIM\$CGRX, in a partition on the VSE machine. Please see the BIM\$CGRX text file for more information.

The following variable shown above must be used and is described as follows:

IMOD - Name of the IMOD to be executed. For IMOD execution, this must be BIMTCPRX.

You must make sure that IMOD is the first variable and should remain hidden.

The second IMOD (type="TEXT") needs to contain the name of the actual IMOD you wish to execute, along with any arguments for that IMOD. This will be input, or included within the value="" for this field.