

HIGH TEMPERATURE CAMERAS FOR INDUSTRIAL APPLICATIONS



MIRION

CAMERAS	A CONTRACTOR	M530™ Lynx Color Camera	Visible Light Color Camera; enables the flexibility to customize electronics, lenses, filters and other options to provide continuous monitoring. Straight, oblique, or right angle lens tube options available. Compatible with M721 Iris Controller. Additional water cooling available.	1 11 1			
		M535™ Lynx Viewing Camera System	Visible Light Color Camera; enables the flexibility to customize electronics, lenses, filters and other options to provide continuous monitoring. Straight or oblique lens tube options available. Includes temperature sensors.				
	A CONTRACTOR	M540 [™] Lynx Near IR Viewing Camera System	Near IR Black and White Camera with flexibility to customize electronics, lenses, filters and other options. Able to penetrate gaseous and fine particulate i nterferences. Straight, oblique, or right angle lens tube options available. Additional water cooling available.				
	<u>a</u>	M555 [™] Spyrometer® Temperature Measurement	Patented combination of color video camera and scanning pyrometer*; monitors process conditions while measuring the temperature of any area in the field of view. Video image and temperature information are displayed on a VGA monitor. Additional water cooling available.	X			
		M560™ IR Camera	Combines mid-wave imaging core technology with an optional calibrated optical pyrometer. Optimizes the clarity of monitoring slag build-up, smeltbed profile, or product distribution and burn efficiency.				
PROCESSORS	A real	M215 S [™] Spyrometer [®] Processor	Supports one or two Mirion cameras, giving the ability to view processes from two locations. Application software provides up to 32 overlaid temperature measurement zones per camera, fully adjustable for size and measurement mode.				
	A real	M610 S™ Calico 3 Temperature Measurement System	Supports one or two Mirion cameras, providing precise temperature measurement across the screen, eliminating erroneous measurements at the edge of the image. Measures up to 32 'free form' temperature measurement zones.	ANK .			
		M704 [™] Viewing Pyrometer	Temperature data is multiplexed with the video signal and sent to the M704 unit. It separates them and displays the video on a monitor with a locater square on the screen, colorizing the image and providing contrast expansion.				
	o) / Hu Mizimar Mi	M721 [™] Auto Iris Controller	Allows adjustments to be made to the M530 camera auto- iris from the control room, retaining flame details and burne viewing quality. Connection is made via the same coax cab that is normally run from the camera to the control room.				
COMMON ACCESSORIES		M356 [™] Retract	Retracts the camera from the most severe heat, protecting it from serious damage where the plant supply of air pressure, water or electricity has been interrupted. Includes ruggedized safety air reservoir and additional options.				
		M408 [™] Air Filter System	Provides clean air in industrial environments where there is a higher air contaminate content level and where local control and regulation of the air supply to the camera is required.				

*USA Patent 6,667,761

Mirion at your service

High temperature industrial cameras from Mirion have been helping operators and engineers optimize and remotely view kilns, boilers, furnaces and glass tanks since the 1980s. Our systems combine temperature measurement, real-time video, and image processing into an enhanced video experience showing measurement information overlaid onto a live video image.





Cement





Waste-To-Energy Plants

From the largest military force, nuclear-related and specialized industries, to the small size medical office next door, Mirion has the strength and presence to serve our customers. Our Customer Care Teams are committed to providing outstanding support and delivering excellence in every interaction.

Pulp and Paper

Thermal Power and Auxiliary Boilers





Other High Temp Applications

Mirion Technologies is a leading provider of innovative products, systems and services related to the measurement, detection and monitoring of radiation.

				Cement, Lime and other Rotary Kilns	Clinker and other Grate Coolers	Chemical Recovery and Fluidized Bed Boilers	Steel and Aluminium Furnaces	Thermal Power and other Auxiliary Boilers	Waste to Energy Plants	Other
CAMERAS		M530™ Lynx Color Camera	Visible Light Color Camera; enables the flexibility to customize electronics, lenses, filters and other options to provide continuous monitoring. Straight, oblique, or right angle lens tube options available. Compatible with M721 Iris Controller. Additional water cooling available.	-	✓	✓	1	 Image: A second s	✓	<
		M535™ Lynx Viewing Camera System	Visible Light Color Camera; enables the flexibility to customize electronics, lenses, filters and other options to provide continuous monitoring. Straight or oblique lens tube options available. Includes temperature sensors.	-	<	-	1	 Image: A start of the start of	✓	√
	A CONTRACTOR	M540 [™] Lynx Near IR Viewing Camera System	Near IR Black and White Camera with flexibility to customize electronics, lenses, filters and other options. Able to penetrate gaseous and fine particulate i nterferences. Straight, oblique, or right angle lens tube options available. Additional water cooling available.			•		✓		
	A CONTRACTOR	M555 [™] Spyrometer® Temperature Measurement	Patented combination of color video camera and scanning pyrometer*; monitors process conditions while measuring the temperature of any area in the field of view. Video image and temperature information are displayed on a VGA monitor. Additional water cooling available.	-	✓	-		 Image: A start of the start of	<	
	A COL	M560™ IR Camera	Combines mid-wave imaging core technology with an optional calibrated optical pyrometer. Optimizes the clarity of monitoring slag build-up, smeltbed profile, or product distribution and burn efficiency.			-		 Image: A start of the start of		
PROCESSORS	R THE	M215 S [™] Spyrometer® Processor	Supports one or two Mirion cameras, giving the ability to view processes from two locations. Application software provides up to 32 overlaid temperature measurement zones per camera, fully adjustable for size and measurement mode.	-	1	-	1	 Image: A start of the start of	<	1
	A real Array	M610 S™ Calico 3 Temperature Measurement System	Supports one or two Mirion cameras, providing precise temperature measurement across the screen, eliminating erroneous measurements at the edge of the image. Measures up to 32 'free form' temperature measurement zones.			-		 Image: A start of the start of		
	1.13 To exercise	M704 [™] Viewing Pyrometer	Temperature data is multiplexed with the video signal and sent to the M704 unit. It separates them and displays the video on a monitor with a locater square on the screen, colorizing the image and providing contrast expansion.			-		✓		
	o, Arte , o Myziataw M	M721 [™] Auto Iris Controller	Allows adjustments to be made to the M530 camera auto- iris from the control room, retaining flame details and burner viewing quality. Connection is made via the same coax cable that is normally run from the camera to the control room.	1	1	✓	1	 Image: A start of the start of	<	1
COMMON ACCESSORIES		M356™ Retract	Retracts the camera from the most severe heat, protecting it from serious damage where the plant supply of air pressure, water or electricity has been interrupted. Includes ruggedized safety air reservoir and additional options.	1	•	-	1	 Image: A start of the start of	<	1
		M408 [™] Air Filter System	Provides clean air in industrial environments where there is a higher air contaminate content level and where local control and regulation of the air supply to the camera is required.	1	1	✓	1	 Image: A start of the start of	✓	✓

*USA Patent 6,667,761









www.mirion.com

Copyright © 2020 Mirion Technologies, Inc. or its affiliates. All rights reserved. Mirion, the Mirion logo, and other trade names of Mirion products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned, including Bluetooth, are the property of their respective owners.