
Echo Eliminator - Bass Buster

Bonded Acoustical Cotton Low Frequency Absorber Panels









FEATURES & BENEFITS

- Low Frequency High Performance
- Durable
- User Friendly
- May contribute toward LEED® Credits

MATERIAL

1.5 lb. density, recycled bonded acoustical cotton fiber

FFATURES

Exceptionally good low frequency absorption. Ideal behind acoustical fabric, perforated or slotted panel surfaces

APPLICATIONS

Industrial, architectural or pro audio applications. Machinery and mechanical rooms. For harsh noisy environments that require high performance, low frequency noise reduction. Above acoustical ceiling grid systems. User friendly alternative to glass fiber insulations

THICKNESS

4"

SIZES

24" x 48" (Special sizes available upon request based on minimum quantities).

FLAMMABILTY

Class A Fire Rated per ASTM E84

COLOR

Gray

INSTALLATION

Adhesive, mechanical clips, friction fit

Test Reports & Additional Information Can be Found at:

https://www.acousticalsurfaces.com/baffle_options/sanitary_baffles.htm

Echo Eliminator - Bass Buster - Acoustical Performance

Frequency	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	NRC
Absorption Coefficient	0.97	1.37	1.23	1.05	1.00	1.01	1.15









ACOUSTICAL SURFACES, INC.

Celebrating Over 40 Years – SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION SPECIALISTS! 952.448.5300 | 800.448.0121 | sales@acousticalsurfaces.com | www.acousticalsurfaces.com