

B A F F L E S **Poly Max**

STOP NOISE

ACOUSTICAL
SURFACES INC.

SOUND ABSORPTION MADE EASY!

Poly Max™ Baffles

Poly Max polyester acoustical Baffles are non-allergenic, non-toxic, fungal-resistant, and do not contain chemical irritants or formaldehyde. Decorative and tackable, these acoustic ceiling baffles are available in a variety of colors and can be printed with custom graphics to blend into any décor. Material: 100% polyester (60% PET-recycled fiber, 40% PET-virgin fiber)

Applications:

Theaters, gymnasiums & multipurpose rooms, commercial & office buildings, studios & production houses, pro audio, restaurants & night clubs, government & municipal buildings, hospitals & medical clinics, schools & universities, houses of worship, industrial & manufacturing facilities and much more

SIZES & OPTIONS

Standard Sizes: 24" x 48", 48" x 96"

Cut To Size/Custom Up to 48" x 96"

Thickness/Density: 1/2" thick/12.5 lb. per cubic foot (pcf);

1" thick/7.5 lb. pcf; 2" thick/5 lb. pcf

Grommets available for 1/2" and 1" thick baffles

Eyelet hooks available for 1" and 2" thick baffles

COLORS



Red White Orange Lime Blue Purple



Beige Tan Silver Black Gray

Printed graphics available! Call for information

ACOUSTICAL PERFORMANCE

ASTM C423 A-Mount: 1/2": 0.40 NRC; 1": 0.70 NRC;

2": 0.95 NRC

FLAMMABILITY

Class A Fire-Rated per ASTM E84



INSTALLATION

To install Poly Max Cloud panels, loop suspension cable (by installer) through factory installed eyelet or grommet in panel and close the loop with a cable clamp or similar hardware. Suspension cable is to be anchored to the roof deck or ceiling structure as necessary.



ACOUSTICAL | SURFACES, INC.

Celebrating Over 35 Years – SOUNDPROOFING, ACOUSTICS, NOISE & VIBRATION SPECIALISTS

952.448.5300 | 800.448.0121 | sales@acousticalsurfaces.com | www.acousticalsurfaces.com

© 2020 Acoustical Surfaces, Inc. V1