

Fast Break

Drying Agent

DESCRIPTION

One of our newest members to the drying agent family, this highly concentrated product offers big time results with minimal usage. It was designed to meet increasing need for high flash drying agents while not sacrificing drying performance.

This product offers no frills, but works consistently every time.

USAGE INSTRUCTIONS

This product is ideally applied under low pressure application in tunnel and in-bay automatic settings. Begin application at 1000-1500:1 (4-6 drops). For high pressure application apply at 2000-3000:1 (2-3 drops). In applications where greater amounts of rinse water are applied to the vehicle stronger dilutions of may be required.

FEATURES

- Rapidly beads water
- Consistently works in all applications
- High flash point
- Highly concentrated for minimal usage


SIZES AVAILABLE

- | | |
|-----------------|--------------------|
| 5-gallon pails | Code: 10-50117-005 |
| 15-gallon drums | Code: 10-50117-015 |
| 30-gallon drums | Code: 10-50117-030 |
| 55-gallon drums | Code: 10-50117-055 |

SPECIFICATIONS

COLOR:	YELLOW
FRAGRANCE:	NONE
FOAM:	NONE
PH:	7-8

Drop Count (Titration)	Oz/Gal of water	Ratio to 1
1	.06	2303
2	.11	1151
3	.17	767
4	.22	575
5	.28	460
6	.33	383
7	.39	328
8	.44	287
9	.50	255
10	.56	229
11	.61	208
12	.67	191



**ANYTHING
BUT ORDINARY**