

HuddleCamHD

Compatibility

- VISCA Protocol
- PELCO-D
- PELCO-P

What's in the box?

- Three-Axis Joystick
- RS232 cable
- DC12V Power Supply
- User Manual

Features

- Durable Metal Housing
- RS232, RS485, & RS422
- On Screen Display Menu control
- Variable Pan, Tilt, Zoom, & Focus speed control
- Iris, Focus, & Preset control
- 6) Camera Quick Select keys
- 9) Quick Preset Set & Call keys

Model Number: HC-JOY-G3

Easy pan, tilt, & zoom control for any VISCA or PELCO protocol camera!
Adjust pan, tilt, zoom, & focus speeds.
Use 3-dimensional joystick with "twist" for zoom control



1. LCD Display

Menu options are displayed here

2. Lens Control

Focus+/-, Focus Lock/Unlock, Iris +/-, Auto Focus & Exposure

3. Joystick

Three-axis joystick controller

4. Camera Quick Select

Quickly swap between first 6 cameras

5. Preset & OSD Control

Allows for preset, speed, & OSD control

6. Numeric Keys

Numeric keys for presets, changing parameters, and more

7. DB9 Connection

Allows for RS232 through DB9 connections

8. Phoenix Connection

Allows for RS422 or RS485 wiring connections

9. Power Connection

DC12V Power Connection

Key Technical Specifications

Connections:	RS232, RS485, RS422
Baud Rate:	1200-19200 bps
Interfaces:	DB9: RS232; 5SCT: RS485/RS422
Max Cameras:	Control up to 255 Cameras
Max Presets:	Up to 255 Presets
Max Distance:	3,937' (1200m) using 24 gauge twisted pair

Operation Specifications

Power:	6W (12VDC Voltage)
Working Temp:	14° ~ 122° F (-10° ~ +50° C)
Working Humidity:	10 ~ 90% (non-condensation)
Weight:	3.4 lbs 1.6 kg
Dimensions (in.):	12.6W x 4.3H x 7.1D
Dimensions (mm.):	320W x 109H x 180D