

HuddleCamHD HuddleView

Auto Framing Camera Solution

The HuddleCamHD HuddleView is your simple auto framing solution.

Model Number:

HC12X-HUDDLEVIEW

<https://huddlecamed.com/huddleview/>

KEY FEATURES

- 12X Optical Zoom
- Motion & Facial Framing
- RSTP / RTMP Streaming
- Multiple Video Outputs
- 1080p@60 FPS SDI Feed
- 1080p@60 FPS IP Feed
- 72.5° Field of View
- Software Interface
- Supported VISCA Protocol & VISCA over IP
- Photobooth Functionality
- Control Zones
- Control Zone Triggers



WHAT'S IN THE BOX

- 12X HuddleView Camera
- Power Supply
- IR Remote
- RS-232 Control Cable
- USB 3.0 Cable 3m / 9.8 feet
- Setup Documents

1. Tracking Lens

12X Optical Zoom

2. Reference Lens

86° HFoV

3. TF Slot

Allows for Photobooth Functionality

4. Audio Input

3.5mm audio embedding connector

5. Network Connection

10/100 Ethernet port

6. DVI-D Connection

Provides simultaneous 1080p@60 FPS

7. 3G-SDI Connection

Provides simultaneous 1080p@60 FPS

8. VISCA Input Connection

For connecting 3rd party joystick

9. USB 3.0 Connection

Provides simultaneous 1080p@60 FPS

10. DC12V Power Connection

For powering the camera

Tracking Camera Image Sensor & Lens

Video Sensor	1/2.8" EXMOR, 2.14 Mega Pixel
Frame Rate	60fps @ 1920x1080p
Lens Zoom	12X Optical, f=3.9-46.8mm
Field of View	6.3° (tele) to 72.5° (wide) Horizontal
Min Lux	0.5 lux

Reference Camera Image Sensor & Lens

Video Sensor	1/2.8" EXMOR, 2.14 Mega Pixel
Field of View	86° (Horizontal) x 52° (Vertical)
Lens	2.4mm

Pan / Tilt Movement

Pan Movement	±170°
Pan Speed	0.1° to 120° /s
Tilt Movement	-90° to -30°
Tilt Speed	0.1° to 90° /s
Presets	256 Presets

Electrical Index

Power Supply	12V D 2.5A
Input Power	20W (Max)
PoE	No supported

Physical Specifications

Material	Aluminum, Plastic
Color	Gray
Dimensions (W x D x H)	9.6" x 5.7" x 6.4" 243mm x 145mm x 163mm
Weight	2.64 lbs (1.2 kg)
Working Environment	Indoor
Operating Temperature	32°F to 104°F (0°C to 40°C)
Storage Temperature	-4°F to 140°F (-20°C to 60°C)
Humidity Range	10% - 80%

Rear Board Connectors

HD Video Interfaces	3G-SDI, USB 3.0, DVI-D
Controller Signal Interface	8pin mini-din
Audio Input Interface	3.5mm
Network	10/100
Power Supply Interface	D12V 2.5A

Warranty

Mfg. Warranty	3 Years Parts & Labor
---------------	-----------------------