

## PTZOptics

### 4D IP Joystick Controller

Model Number: PT-JOY-G3

#### Compatibility

- VISCA over IP protocol
- All PTZOptics Cameras
- Other VISCA over IP cameras

#### What's in the box?

- Four-Axis Joystick
- 12V DC Power Supply
- User Manual

#### Main Features

- Durable Metal Housing
- VISCA over IP protocol
- Auto-Search network
- Real time status display
- Pan, Tilt, Zoom Control
- Pan & Tilt Speed Control
- PoE (802.3af)
- Assignable Control Port

Auto-search your network for VISCA over IP compatible devices. Use any pan, tilt & zoom controls for any or multiple VISCA over IP protocol cameras! Controls pan, tilt & zoom with variable speeds. For best results, pair with a PTZOptics camera.



- |   |   |  |
|---|---|--|
| <p><b>1. LCD Display</b><br/>Menu options displayed here</p> <p><b>2. Joystick</b><br/>Three-axis joystick controller</p> <p><b>3. Camera Quick Select</b><br/>Quickly swap between 6 cameras</p> <p><b>4. PTZ &amp; Preset Control</b><br/>Adjust PTZ speed, set &amp; call presets, &amp; modify OSD menu</p> | <p><b>5. Numeric Keys</b><br/>Numeric keys for presets, changing parameters, &amp; more</p> <p><b>6. Camera Image Control</b><br/>Adjust Iris, auto focus, &amp; auto exposure</p> <p><b>7. Focus Control Keys</b><br/>Focus+, Focus-, Auto Focus on/off</p> <p><b>8. VISCA Connections</b><br/>VISCA connections are not supported on this model</p> | <p><b>9. RJ45 Connection</b><br/>Used for IP and PoE (802.3af) Connection</p> <p><b>10. Power Connection</b><br/>12V DC Power Connection</p> |
|---|---|--|

#### Key Technical Specifications

Connections	RJ45 Network Connection
Maximum Cameras	Control up to 253 Cameras
Maximum Distance	328 Ft. (100 meters) cable length to nearest LAN switch

#### Other.

Warranty	2 Year
----------	--------

#### Operation Specifications

Power	5W (12VDC Voltage) or PoE (802.3af)
Working Temp	32° F ~ 131° F (0° ~ 55° C)
Working	10 ~ 90% (non-condensation)
Weight	3.3 lbs   1.5 kg
Dimensions (in.)	12.6W x 7.1H x 4.3D
Dimensions	320W x 181H x 110D