WEBCAM

Model Number:

PT-WEBCAM-80 http://ptzoptics.com/webcam/

PTZOPTICS


Webcam

The PTZOptics webcam is an easy to use, Plug-and-Play camera with USB 2.0 connectivity and power.

KEY FEATURES

- 1920x1080p @ 30 fps
- Plug and Play USB Power
- 80° Field of View
- USB 2.0
- OSD Menu Software
- EPTZ Control





1. Lens

80° Field of View lens

4. Lens Cover

Rubber lens cover for when camera is not in use

2. LED Indicator

LED is illuminated during use

5. Mounting Base

To mount camera to monitor or 1/4 20 screw

3. Microphone Array

Beamforming microphones for high quality pickup

6. USB 2.0 Cable

For connection to PC USB 2.0 port

Image Sensor & Lens	
Video Sensor	1/2.7" CMOS, 2.07 Mega Pixels
Resolution	1080p-30/25, 720p-30/25
Frame Rate	Up to 30 fps (MJPEG)
Lens	Focus: f=2.8mm
Field of View	80°
Min. Illumination	0.05 Lux @ (F1.8, AGC ON)
Digital Noise Reduction	2D, 3D DNR
EPTZ Digital Zoom	1x - 8x
Electronical Index	
Input Voltage	5V (USB Power)
Current Consumption	270mA
Power Consumption	1.4W
Working Environment	Indoor

MaterialPlasticDimensions (in.)4.6"W x 1.5"H x 1.2"D (not including bracket)Dimensions (mm)118 x 37.2 x 30.8 (not including bracket)Weight0.36 lbs (0.16 kg)Box Dimensions5.4"W x 3.1"H x 3.0"D (137 x 79 x 76)Boxed Weight0.4 lbs (0.18 kg)Operating Temperature14°F to 104°F (-10°C to 40°C)Storage Temperature-40°F to 140°F (-40°C to 60°C)Rear Board ConnectorsVideo/Power InterfaceUSB 2.0	Physical Specifications	
Dimensions (mm) 118 x 37.2 x 30.8 (not including bracket) Weight 0.36 lbs (0.16 kg) Box Dimensions 5.4"W x 3.1"H x 3.0"D (137 x 79 x 76) Boxed Weight 0.4 lbs (0.18 kg) Operating Temperature 14°F to 104°F (-10°C to 40°C) Storage Temperature -40°F to 140°F (-40°C to 60°C) Rear Board Connectors Video/Power Interface Video/Power Interface USB 2.0	Material	Plastic
Weight 0.36 lbs (0.16 kg) Box Dimensions 5.4"W x 3.1"H x 3.0"D (137 x 79 x 76) Boxed Weight 0.4 lbs (0.18 kg) Operating Temperature 14°F to 104°F (-10°C to 40°C) Storage Temperature -40°F to 140°F (-40°C to 60°C) Rear Board Connectors Video/Power Interface Video/Power Interface USB 2.0	Dimensions (in.)	4.6"W x 1.5"H x 1.2"D (not including bracket)
Box Dimensions 5.4"W x 3.1"H x 3.0"D (137 x 79 x 76) Boxed Weight 0.4 lbs (0.18 kg) Operating Temperature 14°F to 104°F (-10°C to 40°C) Storage Temperature -40°F to 140°F (-40°C to 60°C) Rear Board Connectors Video/Power Interface USB 2.0	Dimensions (mm)	118 x 37.2 x 30.8 (not including bracket)
Boxed Weight 0.4 lbs (0.18 kg) Operating Temperature 14°F to 104°F (-10°C to 40°C) Storage Temperature -40°F to 140°F (-40°C to 60°C) Rear Board Connectors Video/Power Interface USB 2.0	Weight	0.36 lbs (0.16 kg)
Operating Temperature 14°F to 104°F (-10°C to 40°C) Storage Temperature -40°F to 140°F (-40°C to 60°C) Rear Board Connectors Video/Power Interface USB 2.0	Box Dimensions	5.4"W x 3.1"H x 3.0"D (137 x 79 x 76)
Storage Temperature -40°F to 140°F (-40°C to 60°C) Rear Board Connectors Video/Power Interface USB 2.0	Boxed Weight	0.4 lbs (0.18 kg)
Rear Board Connectors Video/Power Interface USB 2.0	Operating Temperature	14°F to 104°F (-10°C to 40°C)
Video/Power Interface USB 2.0	Storage Temperature	-40°F to 140°F (-40°C to 60°C)
VAL 210	Rear Board Connectors	
	Video/Power Interface	USB 2.0
Other	Other	
Mfg. Warranty 5 Years Parts & Labor	Mfg. Warranty	5 Years Parts & Labor