



RESIDENTIAL Flex-Tube® PV

FLEXAUST

Coextruded Clear PVC hose with black PVC helix

(Medium Weight)

- Economical
- Ultra smooth interior, crush resistant
- OEM lengths and colors available
- Wall thickness .035"

| SIZE | 4", 5", 6", 7", 8", 10", 12" |
|-------------|------------------------------|
| LENGTH | 12", 25" |
| TEMP. RANGE | 20° to 160° |

Flex-Tube® PU

(Medium Weight)

Coextruded clear thermoplastic ether based polyurethane with rigid yellow ABS helix

- Great abrasion resistence
- Ultra smooth interior, crush resistant
- Puncture / tear resistant
- OEM Lengths and colors available
- Wall thickness .035"

| ,, | |
|-------------|------------------------------|
| SIZE | 4", 5", 6", 7", 8", 10", 12" |
| LENGTH | 12", 25" |
| TEMP. RANGE | -40° to 200° |

Flex-Tube® PU (Medium Weight)

Specially designed stainless steel band and welded stainless steel bridge with carbon steel screw.

- · Fits over helix creating a leak proof seal
- Available in sizes 4" to 12"



COMMERCIAL Flexadux®LCDC

(Medium Weight)

High performance polypropylene blend hose reinforced with a spring steel wire helix and external polypropylene wearstrip

- Economical
- Light weight, drag resistant
- Long flex life with good abrasion and tear resistance
- Wall thickness .032"

| SIZE | 8", 10", 12" |
|-------------|--------------|
| LENGTH | 10", 25" |
| TEMP. RANGE | -30° to 200° |

Flexadux @ HT-W

(Heavy Weight)

Coextruded clear thermoplastic ether based polyurethane with rigid yellow ABS helix

- Great moisture and UV resistance
- External wearstrip offers additional drag resistance
- Puncture and tear resistant
- Wall thickness .035"

| SIZE | 8", 10", 12" |
|-------------|--------------|
| LENGTH | 10", 25" |
| TEMP. RANGE | -60° to 270° |



MUNICIPAL Flx-Thane®HD

(Heavy Weight)

Polyurethane hose reinforced with a bronze coated spring steel wire helix.

- Superior abrasion resistance & tear strength
- Ideal for leaf and debris collection
- Great moisture and UV resistance
- Excellent flexibility
- Also available in translucent blue
- Wall thickness .045"

| SIZE | 12", 14", 16", 18" |
|-------------|--------------------|
| LENGTH | 10", 25" |
| TEMP. RANGE | -65° to 200° |

Flexadux® HT-W Coextruded clear

(Very-Heavy Weight)

thermoplastic ether based polyurethane with rigid yellow ABS helix

- Great abrasion resistance & higher tear strength
- Severe service & debris collection
- Great moisture and UV resistance
- Also available in translucent blue
- Wall thickness .060"

| SIZE | 12", 14", 16", 18" |
|-------------|--------------------|
| LENGTH | 10", 25" |
| TEMP. RANGE | -65° to 270° |

All Leaf Collection Hoses In Stock for the Season!







OnGuard Asset Tracker has Maintenance Programs to **Improve Hose Safety**

Reduce the risk of hose failures through routine hose inspections, testing and certification programs. Our OnGuard™ hose management services include testing, tagging and traceability of your hoses from "cradle to grave". These proactive programs are managed by our hose experts and keep you running efficiently and safely.

TEST.

TAG.

TRACK.

Our Products

- Hose Reels
- Industrial Hose
- Hydraulic Hose
- Metal and PTFE Hose
- Gangway & Load Arms
- Accessories
- Gaskets

- Air & Multipurpose
- Food & Beverage
- Chemical Hose
- Petroleum Hose
- Materlial Handling
- Steam Hose
- Water Hose











Premier Suppliers





























