



RESIDENTIAL Flex-Tube® PV

Coextruded Clear PVC hose with black PVC helix

(Medium Weight)

- Economical
- Ultra smooth interior, crush resistant
- OEM lengths and colors available
- Wall thickness .035" 4" 5" 6" 7" 8" 10". 12

SIZE	4,5,0,7,8,10,12
LENGTH	12", 25"
TEMP. RANGE	20° to 160°

Flex-Tube® PU

(Medium Weight)

Coextruded clear thermoplastic ether based polyurethane with rigid yellow ABS helix

- Great abrasion resistence
- Ultra smooth interior, crush resistant
- Puncture / tear resistant
- OEM Lengths and colors available
- Wall thickness .035"

SIZE	4", 5", 6", 7", 8", 10", 12"
LENGTH	12″, 25″
TEMP. RANGE	-40° to 200°

Flex-Tube® PU

(Medium Weight)

Specially designed stainless steel band and welded stainless steel bridge with carbon steel screw.

- Fits over helix creating a leak proof seal
- Available in sizes 4" to 12"



COMMERCIAL **Flexadux®LCDC**

(Medium Weight)

High performance polypropylene blend hose reinforced with a spring steel wire helix and external polypropylene wearstrip

- Economical
- Light weight, drag resistant
- Long flex life with good abrasion and tear resistance
 - Wall thickness .032"

SIZE	8", 10", 12"
LENGTH	10″, 25″
TEMP. RANGE	-30° to 200°

(Heavy Weight)

helix

- Great moisture and UV resistance
- External wearstrip offers additional drag resistance
- Puncture and tear resistant
- Wall thickness .035"

SIZE	8", 10", 12"
LENGTH	10″, 25″
TEMP. RANGE	-60° to 270°
	- / -



MUNICIPAL Flx-Thane®HD

(Heavy Weight)

Polyurethane hose reinforced with a bronze coated spring steel wire helix.

- Superior abrasion resistance & tear strength
- Ideal for leaf and debris collection
- Great moisture and UV resistance
- Excellent flexibility
- Also available in translucent blue
 - Wall thickness .045"

SIZE	12", 14", 16", 18"
LENGTH	10", 25"
TEMP. RANGE	-65° to 200°

Flexadux® HT-W Coextruded clear thermoplastic ether (Very-Heavy Weight) based polyurethane with rigid yellow ABS helix

- Great abrasion resistance & higher tear strength
- Severe service & debris collection
- Great moisture and UV resistance
- Also available in translucent blue
- Wall thickness .060"

SIZE	12", 14", 16", 18"
LENGTH	10″, 25″
TEMP. RANGE	-65° to 270°

All Leaf Collection Hoses In Stock for the Season!

Flexadux® HT-W Coextruded clear

thermoplastic ether based polyurethane

with rigid yellow ABS





OnGuard Asset Tracker has Maintenance Programs to Improve Hose Safety

Reduce the risk of hose failures through routine hose inspections, testing and certification programs. Our OnGuard[™] hose management services include testing, tagging and traceability of your hoses from "cradle to grave". These proactive programs are managed by our hose experts and keep you running efficiently and safely.

TEST.

TAG.

TRACK.

Our Products

- Food Grade Industrial Hose
- Sanitary Hose Assemblies
- Acid & Chemical Transfer
- Metal Hose
- PTFE Hose
- Petroleum Transfer
- Material Handling
- Ducting Hose
- Clean Up Hose
- Steam Hose

- Water Industrial Hose
- Air Hose
- Fire / Mill Hose
- PVC Tubing & Hose
- Ultra-High Pressure Hydraulic Hose
- Medium Pressure Hydraulic Hose
- Cam & Groove Fittings

Stucchi

Sanitary Adapters & Clamps









Premier Suppliers



Ellwood City, PA 16117





AmericanBiltrite











ADDRESS: 1655 RT 65



800 242 1670 WWW.ALLIEDRUBBER.COM