

Touchscreen - 100 / POE / Connect-4

Manufacturers Details

Atamate Ltd
Old House
The Ridings
Oxford
OX3 8TB
UK

Tel: +44 1865 920 101

www.atamate.com



Overview

Hub Edge computer for small installations with integral 7" touchscreen.

Processing

The Touchscreen is a small but powerful Hub computer running a Linux operating system and Atamate software. It includes a 7 inch (~18cm) touchscreen that can be used for controlling the installation. Optionally it includes 4No. AUX connectors for connecting to Atamate hardware via I2C serial links or digital I/O, (1No. AUX also has RS485 capability for Modbus, Profibus) There is also an option for POE power so that only one CAT5/6 cable needs to be run to the gateway, instead of the standard CAT5/6 cable for data with an additional power cable.

Power

100-250Vac, UK 13A plug power supply unit (supplying 5.1Vdc 3A via USB-C connector). Power over Ethernet (PoE to IEEE 802.3af) option which also includes a cooling fan.

Touchscreen - 100 / POE / Connect-4

Installation Information

The Touchscreen can be installed by any qualified electrician.

The Touchscreen is powered from a small plug-in power supply unit or a POE connection from a local network switch. The Touchscreen relies on convection air currents for cooling so needs good free air movement (PoE version includes a fan).

Mounted on a vertical surface over a standard UK electrical double backbox (>35mm deep).

Cable entry from the side and top of the unit.

Requires connection to the LAN, HAN and power supply unit (if not POE).

Environmental

Humidity: 10 to 90% RH

Temperature: 5 to 40 C

Water/dust protection: IP20

The Touchscreen is part of an Atamate smart building installation.

This is to be designed and commissioned by Atamate Partners.

