

ALM 3230 Automatic Laminator

SELECTION ♦ SOLUTIONS ♦ SIMPLICITY

Laminates paper up to 100 lb cover stock

Virtually Unattended Operation



- Small Foot Print less than 4 sq. ft.
- Table Top or optional stand with locking roller casters
- 115 Volt, 15 amp service with economy mode
- Ultra guick warm up of less than 5 minutes
- Sheet sizes: 13"x19", 12"x18", 11"x17", & 8.5"x11"
- Automatic two side lamination or short one side work
- Adjustable Automatic Flush or Sealed edge trim
- 1 year parts and 90 day labor warranty

ALM Exclusive ASAP Roll Film

- · Perfect for Digital Print technology
- · Anti-static properties

Gloss & matte versions available in the following:

1.5mil, 12.6" x 984 ft 3.0mil, 12.6" x 492 ft 5.0mil, 12.6" x 328 ft

1.2mil, 12.6" x 984 ft, Nylon

SPECIFICATIONS:	
Model No.:	ALM 3230
Laminating Speed:	20"- 44"/min.
Temperature Range:	170-270°F
Ultra Fast Warm-Up Time:	Approx. 5 minutes
Thickness of Objects:	20lb bond - 100lb cover
Paper Feeding Capacity:	100 sheets, Adjustable Paper Guide
Applicable Sizes:	
	Letter Paper Size 8.5" x 11"
	Paper Size 13" x 19"
	Paper Size 12" x 18"
	Tabloid Paper Size 11" x 17"
Trimming Methods:	(2 modes) Flush trim or edge seal for all 4 sides of the print
Operation Panel:	LCD display for start, stop, temperature, and trim settings, leading and trailing edge
Other Features:	Laminated sheet counter; Film tension control, Roller gap lever, Paper thickness
Power Consumption:	900W
Power Supply:	AC 120V (60Hz)
Net Weight:	Laminator: 100 lbs. Stand: 48.5 lbs.
Optional Accessories:	Rolling Stand