

Product Information

Construction:	Monomeric PVC, Acid Free
Main Application:	Protection against abrasion, moisture, UV and constant surface contact
Shelf Life:	Up to 2 years
Storage Conditions:	Stored up to 25°C and up to 50% relative humidity in original packaging.
Adhesive:	25 ± microns pressure sensitive solvent based acrylic (Clear Permanent)
Features:	Floor grade anti slip
Finish:	Deep grain textured matt
Core:	76mm

Features and Benefits

Thick 200mic PVC with a Matt "textured" finish laminating film. Especially great for over laminate floor applications. The textured finish for short term promotions acts as a "non slip" surface. Has passed Australian Standards for both slip and stick.

Thickness

PVC Film Thickness:	200 ± microns
Adhesive Thickness:	25 ± microns
Total Thickness:	225 ± microns
Liner Thickness:	120 gsm single side PE coated paper

Certification - CSIRO Testing: AS4586:2013

Test Method	Results
Wet Pendulum Test	P 2
Dry Floor Friction Test	D 1
Wet / Barefoot Ramp Test	A
Oil - Wet Ramp Test	R 9

Standard Stock Sizes

Codes	Standard sizes	Core	Adhesive
Deep Grain Textured Matt			
L113	1370mm x 45m	76mm	Clear Permanent
L112	1400mm x 45m	76mm	Clear Permanent
L111	1525mm x 45m	76mm	Clear Permanent

* Outdoor life will vary depending on installation technique, location and relative position to the sun.

PLEASE NOTE – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the "information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. The seller shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the information.

Durability



Outdoor vertical applicaiton -
Up to 2 years*
Indoor floor application - Up to
12 months*



For additional information
on this product please
use the above QR Code.

V1.2

ALC

www.alclaminating.com

Australian Laminating Company

Pty Ltd

76 NORTH VIEW DRIVE
SUNSHINE WEST VIC 3020

P: +61 (0)3 9312 7400
F: +61 (0)3 9312 7455

SALES@ALCLAMINATING.COM