

ImagePerfect™ 2572PA Hi-Tack is a white matt polymeric vinyl that has been specifically engineered to adhere to LSE (low surface energy) substrates and/or substrates with a low surface temperature. It incorporates Spandex's PerfectApply technology with a grey tinted permanent adhesive. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco-solvent and solvent inks as well as UV-cured and latex inks.

IP 2572PA

ImagePerfect™ 2572PA Hi-Tack Film has been specifically engineered to adhere to LSE (low surface energy) substrates on which it is generally difficult to create an adhesive bond with the product - e.g. hard plastics, polyamide, water-based car paints, surf boards, motocross bikes, quad bikes, powder-coated metal substrates, etc. It incorporates Spandex's PerfectApply technology, increasing repositionability during application and facilitates a bubble-free finish. Additionally, it is also effective in application to substrates with a low surface temperature. IP 2572PA should be used on flat, non-textured surfaces. It promotes high levels of print quality with remarkable text definition and a large colour gamut to ensure colourful images with vibrant area in-fills. It is equipped with a backing paper that offers excellent lay flat properties.

Laminate: IP 2810-101 gloss or IP 2810-200 matt

Attention: Please make sure the printed IP 2572PA is completely dry before laminating. Before the IP 2572PA is applied, the surface should be completely cleaned.

Specifications	
DESCRIPTION	Polymeric vinyl
COLOUR	White matt (Reach Compliant)
THICKNESS	90µ
WEIGHT	N/A
ADHESIVE	Solvent acrylic, grey hi-tack, permanent
ADHESIVE STRENGTH	30N / 25mm (Finat TM 1/24h)
RELEASE PAPER	Two side PE coated, 160g/m²
TEMPERATURE RANGE	-28°C to +65°C
DURABILITY (UNPRINTED)	Up to 5 years
FLAME RETARDENCY	N/A
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© May 2017 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.

The print media should be completely dry before further processing, such as cutting, laminating, varnishing or application, or the residual solvents can otherwise change the specific features of the product. To ensure the best possible outcome, the match component ImagePerfect™ profile should be used with the relevant ImagePerfect™ media.

