

Polymeric transparent gloss laminate featuring a permanent solvent-based adhesive. This material has been specifically designed for protecting digital prints.

IP 2810-101

Polymeric premium film featuring specific polymeric, non-migrating plasticizers and UV stabilizers, which ensure maximum light fastness and excellent outdoor durability. IP 2810-101 is intended for many flat applications, both interior and exterior, such as markings & decorations, window and vehicle graphics.

This laminate can be used on IP 2501, IP 2502, IP 2503, IP 2504, IP 2505 and IP 2506. It can also be used on many other speciality materials such as IP 2901FR, IP 2903, IP 2905, IP 2906, IP 2909 and IP 2910.

Specifications	
DESCRIPTION	Polymeric laminate
COLOUR	Transparent gloss
FACE FILM THICKNESS	70 μ
WEIGHT	N/A
ADHESIVE	Solvent acrylic permanent
ADHESIVE STRENGTH	20N / 25mm (Finat TM 1/24h)
RELEASE PAPER	PE-coated silicone paper, 140g / m ²
TEMPERATURE RANGE	-30°C to +90°C
DURABILITY (UNPRINTED)	Up to 7 years
FLAME RETARDANCY	Adhered to steel, self-extinguishing
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© January 2007 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.