

ImagePerfect™ 2830-100 is a clear, gloss, PVC laminate with a permanent, solvent-based adhesive system that has been specifically designed for protecting digital prints on perforated window films.

**IP 2830-100**

ImagePerfect™ 2830-100 Perforated Window Film laminate is recommended for use on perforated window films. When applying a perforated window film, it should be applied approximately 6mm from the edge of the window. Apply the laminate over the perforated window film, leaving a gap of 1mm from the edge of the window. This leaves an overlap of 5mm to enhance process security. IP 2830-100 is not suitable for wet applications. This laminate can be used on IP 2701, IP 2703 and IP 2706.

Specifications	
DESCRIPTION	Perforated Window Film laminate
COLOUR	Clear gloss
THICKNESS	70µ
WEIGHT	N/A
ADHESIVE	Solvent based acrylic, permanent
ADHESIVE STRENGTH	12N / 25mm (Finat TM 1/24h)
RELEASE PAPER	Polyester film, 36µ
TEMPERATURE RANGE	-50°C to +110°C
DURABILITY (UNPRINTED)	8 years
FLAME RETARDANCY	N/A
SHELF LIFE	2 years, 20°C / 50% humidity
RECOMMENDATION	For optimum quality, please ensure that the media feed adjustment has been completed for this material

© September 2015 Spandex Group. Technical specifications are subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material for its specific use. All technical data are subject to change.

The durability is based on mid European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the graphics. For instance, exterior performance will be decreased in the case of signs facing south, in areas of long high temperature exposure such as southern European countries, in industrially polluted areas or in areas of high altitude. Also, for horizontal applications, exterior performance will decrease.