

# TexWalk

## Product Data Sheet

### Description

TexWalk is a revolutionary new floor media suitable for a wide range of flooring surfaces indoors & outdoors. Indoors suitable for low pile carpet, stone, lino etc. Outdoors suitable for smooth tiles and smooth concrete etc. TexWalk has a built-in textured non slip surface and does not require an overlamine. No overlamine means it's considerably faster to market plus colours are significantly brighter. Comes with an R12 non slip certification (CSIRO).

### Features

- > Suitable for low pile carpet
- > Suitable for multiple indoor/outdoor surfaces
- > CSIRO approved non slip surface
- > Brilliant print quality
- > No over lamination required
- > Fast through production & fast to market. High volume / fast turn around friendly

Multiple indoor  
outdoor / surfaces

Suitable for  
low pile carpet

Fast production  
turn around

### Applications

- > Retail
- > Exhibitions
- > Shopping centres
- > Office
- > Car Parks
- > Footpaths
- > Concrete walls / columns

Retail

Exhibitions

Car parks

### Surfaces

#### Indoor Floor

- > Carpet (low pile)
- > Concrete
- > Porous Stone
- > Tiles

#### Outdoor Ground

- > Concrete
- > Tiles
- > Asphalt
- > Pavers
- > Porous Stone

Indoor

Outdoor

#### Indoor Wall

- > Plasterboard
- > MDF
- > Concrete

#### Outdoor Wall

- > Concrete
- > Brick

TexWalk is not suitable for ultra smooth surfaces such as polished floorboards, polished stone , glossy tiles etc

### Test First

Every surface is different and changes with time so we recommend trailing with a small piece first in a inconspicuous location. Trial over a minimum 4 week period to determine suitability for the intended surface

# TexWalk

## Printing Methods

- > UV curable
- > Solvent
- > Eco solvent
- > Latex

UV curable

Solvent

Latex

## Durability

TexWalk durability depends on many factors including the surface it is applied to and the frequency of abrasive forces. Please see guide below;

Low Traffic  
4-6 months

High Traffic  
1-3 months

### Indoor Floor

- > Low Traffic - 6 months
- > High Traffic - 3 months

### Outdoor Floor

- > Low Traffic - 4 months
- > High Traffic - 1 month

### Indoor Wall

- > 24 months +

### Outdoor Wall

- > 12 months +

## Slip Resistance

Australian / New Zealand standards AS 4586:2013 approved. CSIRO tested R12 rating

R12

## Storage

Shelf life is 12 months. Store in cool conditions (15-24 degrees C - humidity 40-60% rh)

## Warranty

Since there is no control under which conditions the product has been applied or has been used, all product warranty automatically end as soon as the product has been applied to any surface

## Technical Information

Size Width: 1.22m

Length: 25m & 50m

Foil Fabric with a textured matte vinyl coating (white)

0.10 - 0.25 mm

Adhesive acrylic solvent

Adhesion 80µ +/- 5µ

Total weight 385 g/m<sup>2</sup>

Slip-resistance DIN51130 / BGR 181 R11

Minimum application temperature +10°C / +50°F

visionary digital™

Innovative media for wide format digital printing

Visionary Digital Pty Ltd – Factory 2, 27 William St, Balaclava VIC 3183

Tel.: +61 3 9537 3339

www.visionarydigital.com.au

Email: info@visionarydigital.com.au