

Christy® Pak Arch Saddles

FEATURES

- Available in a wide range of sizes, thicknesses and metallurgies
- High mechanical strength
- Economical
- High available surface area
- Well-proven in thousands of installations world
- Higher hydraulic capacity than first generation metal random packings



PACKING DATA

Nominal	Thickness		*Density		Surface Area		Free Space
	mm	inches (mm)	lbs/ft ³	(kg/m ³)	ft ² /ft ³	(m ² /m ³)	
15	0.012	(0.30)	17.4	(279)	92	(302)	97
25	0.012	(0.30)	13.7	(219)	73	(240)	97
40	0.016	(0.40)	10.4	(167)	49	(161)	97
50	0.016	(0.40)	8.9	(142)	31	(102)	98
60	0.016	(0.40)	7.6	(122)	26	(85)	98
70	0.020	(0.50)	6.9	(110)	19	(62)	99

* Density is based on 304SS.

Christy Catalytics, LLC offers a complete range of catalyst bed supports, tower packings and tower internals.

THE ABOVE DATA ARE BASED ON CONTROLLED TESTING. INDIVIDUAL TEST RESULTS MAY VARY; THEREFORE THESE DATA MAY NOT BE USED FOR SPECIFICATION PURPOSES.

NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, ARE MADE REGARDING THE DATA OR PRODUCTS SHOWN ABOVE.

Revised: March 2021