



## FRONT LOADER

### TZ02D - TE TRACTORS

### TZ04D - TB TRACTORS

The front loader is a compact loader equipment mounted on a 4WD tractor. It is activated by hydraulic cylinders for a multitude of lifting and loading operations and is controlled from the driver's seat. Robust and reliable, it is ideal for digging, plowing and transporting materials. Very useful for all types of work whether on a farm, a garden, on a woodland and others.

#### TECHNICAL DATA

Front loader model			TZ02D	TZ04D
Matching tractor model		hp	TE 25	TB 45-55
Lifting height	H	mm/in	2560 / 100.8	2835 / 111.6
Dumping height	A	mm/in	1850 / 72.3	2140 / 84.3
Overloading height	L	mm/in	2380 / 93.7	2680 / 105.5
Dumping distance	W	mm/in	500 / 19.7	600 / 23.6
Ground clearance	B	mm/in	1210 / 47.6	1360 / 53.5
Max. tip in angle	X	degree°	48	48
Tip out angle	Z	degree°	48	48
Crowd angle	V	degree°	134	134
Digging Depth	S	mm/in	90 / 3.5	95 / 3.7
Lifting force	Q1	kg/lbs	2220 / 4894	2140 / 4718
	Q2	kg/lbs	1470 / 3241	1320 / 2910
Hydraulic pump flow		Gpm	8.5	9.3
Bucket width		mm/in	1350 / 53.1	1500 / 59
Bucket capacity		m <sup>3</sup> /ft <sup>3</sup>	0.2 / 7.06	0.24 / 8.48
Rated lifting capacity		kg/lbs	300 / 661	400 / 882

