

## Personal Teller Machine 10-Series

Providing Your Customers  
with More Transaction  
Options and Helping You  
Integrate Exciting New  
Applications and  
Efficiencies into  
Your Enterprise



## Evolutionary Self-Service

The new 10-Series kiosk is designed for financial institutions working to transition mundane teller transactions to true self-service kiosks that integrate with their core system.

This move enables a full complement of teller transactions and is aligned with the wave of digital transformation initiatives to create the modern branch, with a focus on exceptional client experience.

- 1** 32" Ultra HD Monitor Integrated Touchscreen & Privacy Filter
- 2** Omni-directional barcode Imager
- 3** Hybrid Magstripe / EMV Reader
- 4** NFC Reader
- 5** Encrypted PCI-Compliant PIN Pad
- 6** Biometric Palm Scanner
- 7** Cash Recycler
- 8** MICR Check Scanner with Front/ Back Imager
- 9** Thermal Receipt Printer
- 10** Coin Dispenser
- 11** MICR Check/ Statement Printer



Coin  
Dispensing



Integrated  
Check  
Printer



Cash  
Recycler



UL Certified  
24-Hour  
Safe

## Series 10 Specifications

<b>32' Ultra HD Monitor with Integrated Touchscreen &amp; Privacy Filter</b>	32" TFT-LCD Panel, 3840(x3) x 2160 Resolution Touchscreen - Projective Capacitance Technology	Touchscreen Cover Glass 2.8mm Privacy Filter 60.0° ± 10.0°
<b>Computing System</b>	INTEL i5 (Skylake) 6MB 2.3GHz 35W, RAM 8GB DDR4, Hard Drive, Solid State, 128GB, Long Life	
<b>Wireless Module</b>	Wi-Fi Card Module, 802.11 a/b/g/n, 2.4/5GHz DUAL BAND	
<b>Operating System</b>	Windows 10	
<b>Camera</b>	Resolution 5MP, Auto Focus	
<b>Bulk Note Cash Recycler</b>	<p>Cassette Capacity**  Overall (except reject bin) - 15,000 notes (dispense only) / 13,000 notes (recycle/deposit)  Cassette Capacities ** - 3,000 notes (dispense only) / 2,700 notes (recycle/deposit)  Number of Cassettes - 5  Reject Bin Capacity ** - Approximately 1,000 notes  Acceptable Number of Notes - Maximum 200 notes (Height: 35mm or less). Bunch size can change depending on note condition.  Dispensable Number of Notes - Maximum 200 notes (Height: 35mm or less). Bunch size can change depending on note condition.  Cash Feed Speed - 8 notes per second  ** The capacity shown above is a conversion value of 0.11mm unused notes</p>	
<b>Safe</b>	UL 291 24-hour Service - Level 1 Security Container	
<b>Coin Dispenser</b>	Dispense Only - Up to \$111.42 (USD)	
<b>MICR Check/Statement Printer</b>	Tray 1 - 250 Sheet Capacity Tray 2 - 250 Sheet Capacity	
<b>Check Scanner</b>	Single Document Scan MICR Character Reader: CMC7, E13B Image Resolution - 200 x 200 dpi Gray Level - 8 bit @ 300 dpi Stacker - 150-200 Checks (optional)	
<b>Receipt Printer</b>	Print Technology - Direct Thermal Print Width - 3" Print Resolution - 203 dpi	Print Speed - 7ips Max Media - Approx. 230' on a 2.8" Diameter Roll Cutting Method - Partial Cut
<b>Card Reader</b>	Hybrid Magnetic Stripe/EMV Card Reader EMV Ver4.3 Approved with Anti-skimming Technology	
<b>Pin Pad</b>	Encrypted PIN Pad PCI-Compliant, PCI-PTS 3.x Certified Key Management: Master/Session, DUKPT Encryption Algorithms: AES, DES, and TDES for PIN Encryption	
<b>Biometric Palm Scanner</b>	High Security Authentication Method Utilizing Patented Palm Scanning Technology	
<b>Imager</b>	Omni-Directional Imager - ID and Barcode Scanning	
<b>NFC</b>	NFC Contactless Reader Supporting: ApplePay, Visa, MasterCard, Amex, and others	
<b>Kiosk Controller</b>	Control of Guidance Lights Monitor Vitals of Kiosk System Including: Temperature/Humidity, Security Switches, Receipt Paper Low, Tamper Via Internal Accelerometer	
<b>UPS</b>	700 VA Output Power (utilize to complete current transaction if possible and provide a controlled shutdown of the system)	
<b>Approach Sensor</b>	Adjustable Sensor to Detect and Wake Up Transaction System When a Customer Approaches the Device (distance and walk-by traffic filter configurable)	
<b>Keyboard</b>	USB-Internal (for maintenance purposes only)	
<b>Dimensions</b>	H 51.7", W 17", D 18 (D 15.7" without UPS)	
<b>Weight</b>	Approx. 1400 lbs.	



4205B Westinghouse Commons Drive Charlotte, NC 28273 | 800-922-8501 | [sourcetechnologies.com](http://sourcetechnologies.com)