

CONNECTED ACCESS PORTAL, 2-DOOR CONTROLLER

Cloud-based, credentialed access control.



KEY FEATURES

myQ® Business™
Smart Access Control
Software

CONTROLS
up to 2 Gates/Doors Each

EASILY EXPANDABLE
Network through
myQ® Business™

SMART

MULTIPLE-ENTRANCE CONTROL WITH myQ® Business™.

ELIMINATE WIRING BETWEEN CONTROLLERS IN MULTIPLE-ENTRANCE APPLICATIONS WITH myQ® Business™.

UNIVERSAL COMPATIBILITY WITH 26-, 30- AND 37-BIT WIEGAND-COMPATIBLE READERS, RECEIVERS AND RFID READERS.

EXPANSIVE CAPACITY FOR 25,000 ACTIVE CREDENTIALS STORED LOCALLY SO RESIDENTS CAN ENTER EVEN WHEN THE INTERNET IS DOWN.

REMOTE PROGRAMMING AND ACTIVITY MONITORING USING myQ® Business™.

RELIABLE

EASY TO INSTALL IN NEW OR EXISTING PROPERTIES.

BACKED-UP STORAGE IN myQ® Business™ ENSURES THAT DATABASES ARE NEVER LOST.

POWER OVER ETHERNET (PoE) ALLOWS FOR FLEXIBILITY OF DEVICE PLACEMENT.

SECURE

EMAIL ALERTS LET YOU KNOW WHEN A SUSPENDED CODE IS USED OR IF AN ACTIVE CODE IS BEING OVERUSED.

REAL-TIME ACTIVITY TRACKING WITH myQ® Business™.

CLOUD-BASED SECURITY KEEPS DATA PROTECTED AND SAFEGUARDS RESIDENT INFORMATION.

TOTAL SOLUTION ACCESSORIES:

**CONNECTED ACCESS PORTAL,
HIGH CAPACITY**
Cloud-based access control for
residents and guests.



CAPXL

**CELLULAR 4G/LTE MODEM
WITH WI-FI®**
Makes it easy to connect CAPXL
and CAP2D(s) anywhere.



CAPCELL

PASSPORT RECEIVER
Security+ 2.0® receiver (tri-band 310,
315 and 390 MHz) compatible with
all standard Wiegand protocols.



PWR

PASSPORT REMOTE CONTROLS
PPV3M/PPK3PHM/PPLK1-X
Visor and keychain remotes with
unique credentialed IDs.



PASSPORT

**WIRED KEYPAD AND
PROXIMITY READER**
Single-entry, multifunction controller
that supports up to 2,000 users.



KPR2000

**multiCLASS® SE RP10 MINI
MULLION AND PROXIMITY CARD**
LMC-MINI
Reader and LMPC2-ST Proximity Card
for credentialed access.



PROXIMITY SYSTEM

**RFID LONG-RANGE READER
AND VEHICLE TAGS**
LMSC1000/LMUNTG/LMHNTG
Reader, universal tag (windshield/
headlamp) and hang tag.



RFID SYSTEM

MASTERFUL ENGINEERING.

CAPACITIES



- 2 Controlled Gates/Doors
- 25,000 Local Resident Capacity
- 6,000 Local Event History (FIFO) Offline from Host
- Multiple, Holiday and Hold-Open Scheduling, Including One-Time and Repeating Exceptions
- Compatible Wiegand Formats: 26-, 30- and 37-Bit
- No Facility Code Limitations (1–256 for 26-Bit); “Ignore Facility Code” Option Available

4.5"



3"

1.25"

MECHANICS



- Compact Size Mounts on Standard Single Electrical-Gang Box or in a NEMA Enclosure
- LED Indicator Lights Communicate Status

POWER




- 12VDC, Min. 1.5 Amps (Transformer Not Included)
- PoE (802.3af) Enabled Network Devices, 13 Watts Max.
- UL® Listed



myQ business™

Have more entrances?
Add more CAPXLs or CAP2Ds
to meet the needs of
any community.



CAPCELL or
Modem/Router

Readers



CAP2D



myQ® Business™ subscription required.

STANDARD SPECS.

ELECTRICAL

COMMUNICATION

INTERNET (DYNAMIC OR STATIC IP)

- High Speed
- DSL with at Least 1 MB Download Speed
- Cellular (Optional CAPCELL)

INPUT PORTS

- 2 Wiegand Inputs
- 2 Request-to-Exit (REX) Inputs
- 2 Supervised Inputs

OUTPUTS

- 2 Primary Relays
- 2 Auxiliary Relays

OPERATING TEMPERATURE **-31°F to 150°F**
(-35°C to 66°C)

WARRANTY

- 2-Year

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTON (1)

- 7 1/2" x 5" x 3"
- CAP2D
- Misc. Hardware

For Support Tools and Training Videos, Visit LiftMasterTraining.com

For More Information, Visit LiftMaster.com/AccessControl

Sales Support: **800.282.6225**

Technical Support Center: **800.528.2806**

LiftMasterDealer.CustHelp.com/App/Ask

© 2019 The Chamberlain Group, Inc. All Rights Reserved. LiftMaster, the LiftMaster logo, myQ and the myQ logo are registered trademarks of The Chamberlain Group, Inc. 300 Windsor Drive, Oak Brook, IL 60523 LiftMaster.com

Wi-Fi® is a registered trademark of Wi-Fi Alliance
UL® and the UL logo are trademarks of UL LLC © 2019 All Rights Reserved.
© 2019 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
Copyright © 2019 Phone.com®
LMPAENPG2DXL 2/19