SMOKESHIELD® ELEVATOR

Models ERF10



THE MOST DESIGN FORWARD HOISTWAY SMOKE ENCLOSURE AVAILABLE

LIMITLESS DESIGN FREEDOM

We've applied nearly 100 years of experience in life safety and fire protection to help innovate SmokeShield Elevator. This hoistway closure makes it possible to eliminate the IBC Elevator lobby requirement, and allows the design visionary to pursue more spacious and unique layouts in areas typically requiring elevator lobbies.

SAFETY

SmokeShield Elevator's patented GuideLock™ technology positively re-seals the hoistway after cycling, while the transparency and graphic designs of the curtain itself is both instructional and intuitive for the user in an emergency situation. This i important, because if re-seal does not occur, smoke will migrate and create preventable damage.

AESTHETICS

SmokeShield Elevator is the most design-adaptable hoistway smoke enclosure in the industry. SmokeShield Elevator's design versatility is evident in masonry, dry-wall or other fascia materials, offering the broadest range of mounting possibilities. Any exposed guides or bottom bars can be finished to match, complement, or contrast their surroundings with custom powder coating, or a unique stainless matching guided anodization option.

SECURITY

SmokeShield Elevator's headroom, backroom and sideroom requirements are some of the smallest on the market. Additionally, the control box and battery backup are invisibly located within the headbox.



SMOKESHIELD ELEVATOR KEY FEATURES:

ADDITIONAL AVAILABLE SPACE

SmokeShield Elevator fits into less than 10" of headroom for hoistway openings up to 12' hight and 12' wide

NO VISIBLE FASTENERS >

Our unique guide components seamlessly snap together





CURTAIN RESEALS ELEVATOR

Every time after cycling as a result of our patented GuideLock technology



ADDED CONVENIENCE

A time delay prevents activation during brief power outages

MINIMAL CLEARANCES NEEDED

Control/junction box and batteries are undetectable inside head box



INTUITIVE GRAPHICS

For evacuees and emergency responders ensures simple operation

HIGH VISIBILITY

Through the curtain's transparent material provides an increased safety margin for firefighters and EMTs

OUICK OPENING

Optimally positioned open switch is factory mounted to both sides

BACK-UP

PULL OFF

Emergency lift strap

OPERATION

SmokeShield Elevator deploys upon notification by the fire alarm control panel or local smoke detectors and is re-opened by pushing the curtain-mounted switch or, in the event of complete power loss, by simply lifting the Emergency Lift Strap located at the bottom of the curtain. Patented Guide lock technology ensures a complete hoistway perimeter seal after every cycle.

SmokeShield Elevator automatically resets and autoopens after the alarm is cleared.

STANDARD

24 Hour Battery Backup - Capable of cycling the system for up to 24 hrs.

OPTIONAL

- ► Wire Directly: To emergency back-up source.
- Finishes: Custom powder coat to match architectural and stainless anodized finish guides to match stainless elevator jambs.

Complies with:

- IBC 2003, 2006, 2009, 2012, 2015, 2018
- ICC-ES Report AC 77

Listed:

- UI 1784
- UL 325
- ASTM E84
- ASTM E864

CUSTOM-DESIGNED SOLUTIONS

Contact our experienced Architectural Design Support Team for help in customizing our products to fit your specific application. Call 800.233.8366 ext. 4551 • architecturaldesignsupport@cornellcookson.com www.smokeshieldsmokeandfire.com

