

Formlabs Fuse 1

Quick Stats



| | |
|--------------------------|---|
| Technology | Selective Laser Sintering |
| Build Volume (W x D x H) | 165 x 165 x 300 mm 6.5 x 6.5 x 11.8 in |
| Layer Thickness | 110 microns 0.004 in |
| Build Speed | 10 mm / hour 0.39 in / hour |
| Laser Type | Ytterbium Fiber |
| Laser Spot Size (FWHM) | 200 microns (0.0079 in) |
| Material Refresh Rate | 30% – 50% |

Printing Properties

| | |
|-----------------------------------|---|
| Technology | Selective Laser Sintering |
| Build Volume (W x D x H) | 165 x 165 x 300 mm 6.5 x 6.5 x 11.8 in |
| Layer Thickness (Axis Resolution) | 110 microns .004 in |
| Hopper Capacity | 8.5 kg PA12 nylon 18.7 lb PA12 nylon |
| Material Refresh Rate | 30 – 50 % |
| Dimensions | 685 x 645 x 1065 mm |
| Supports | No supports |

Hardware

Fuse 1

| | |
|---------------------------------------|--|
| Minimum Access Dimensions (W × D × H) | 125.5 × 149.5 × 187.0 cm 49.4 × 59.0 × 73.6 in |
| Printer Dimensions (W × D × H) | 64.5 × 68.5 × 107 cm (165.5 cm with stand) 25.4 × 27.0 × 42.0 in (65.0 in with stand) |
| Weight | 114 kg (without build chamber or powder) 251.3 lb (without build chamber or powder) |
| Startup Time | 60 minutes |
| Operating Environment | 18 – 28 °C 68 – 82 °F ≤ 30% ambient humidity |
| Operating Temperature | 200 °C 392 °F |
| Temperature Control | Quartz tube heating elements Positive temperature coefficient (PTC) cartridges |
| Air Handling | Pressure-controlled two-stage filtration (Replaceable HEPA and carbon mediums) |
| Power Requirements | EU: 230 VAC, 7.5 A (dedicated circuit) US: 120 VAC, 15 A (dedicated circuit) |
| Galvanometers | Formlabs Custom |
| Laser Specifications | Ytterbium Fiber, rated to > 10,000 hrs EN 60825-1: 2014 certified Class 1 Laser Product 1065 nm wavelength Maximum 10 Watts 4.01 mrad beam divergence (nominal, full angle) |
| Laser Spot Size (FWHM) | 200 microns .008 in |
| Radiation Information | The Fuse 1 is a Class 1 Laser product. Accessible radiation is within Class 1 limits. |
| Connectivity | Wi-Fi (2.4 GHz) Ethernet (1000 Mbit) USB 2.0 |
| Printer Control | 10.1" interactive touchscreen 1280 × 800 resolution |
| Alerts | Touchscreen alerts and tracking SMS/email via Dashboard Live video feed with computer vision Proactive maintenance alerts |

Software

| | |
|-----------------------|---|
| Print Preparation | PreForm Desktop Software |
| System Requirements | Windows 7 (64-bit) and up Mac OS X 10.12 and up OpenGL 2.1 4 GB RAM (8 GB recommended) |
| Hardware Requirements | Fuse 1 3D printer |
| File Types | <ul style="list-style-type: none">• .STL or .OBJ• FORM file output |

Formlabs Fuse Sift

Properties



| | |
|--|--|
| Printer Compatibility | Fuse 1 |
| Dimensions | 99.1 × 61.0 × 188.8 cm 39.0 × 24.0 × 61.8 in Height when open: 190 cm (75 in) |
| Fuse Sift Dimensions (W × D × H) | 99.1 × 61.0 × 188.8 cm 39.0 × 24.0 × 61.8 in |
| Build Chamber Dimensions (W × D × H) | 27.9 × 34.2 × 48.9 cm 11.0 × 13.5 × 19.3 in |
| Minimum Access Dimensions (W × D × H) | 221.1 × 122.0 × 218.0 cm 87.1 × 48.0 × 85.8 in |
| Fuse Sift Weight | 93 kg (without build chamber or powder) 205 lb (without build chamber or powder) |
| Build Chamber Weight | 11 kg (17.6 kg, full with 20% packed powder) 24.3 lb (38.8 lb, full with 20% packed powder) |
| Air Filtration Technology | Replaceable HEPA filter |
| Build Volume (W × D × H) | 16.5 × 16.5 × 30.0 cm (with radiused corners) 6.5 × 6.5 × 11.8 in (with radiused corners) |
| Fresh Powder Hopper Capacity | 10.7 kg Nylon 12 23.6 lb Nylon 12 |
| Used Powder Hopper Capacity | 9.8 kg Nylon 12 21.6 lb Nylon 12 |
| Operating Environment | 18 – 26 °C 68 – 80 °F ≤ 30% ambient humidity |
| Air Handling | Negatively pressurized hood with replaceable HEPA filter Independent venting system |
| Air Filtration | Replaceable HEPA medium |

Fuse Sift

| | |
|-----------------------|--|
| Power Requirements | <p>With a vacuum that draws less than 6 A (230 VAC) / 12 A (120 VAC): EU: 230 VAC, 7.5 A (dedicated circuit) US: 120 VAC, 15 A (dedicated circuit)</p> <p>With a vacuum that draws more than 6 A (230 VAC) / 12 A (120 VAC): EU: 230 VAC, 10 A (dedicated circuit) US: 120 VAC, 20 A (dedicated circuit)</p> |
| Vacuum Requirements | Auxiliary vacuum with static dissipative components that is grounded and bonded (e.g., a NFPA 652 compliant vacuum) |
| Connectivity | Wi-Fi (2.4 GHz) Ethernet (1000 Mbit) USB 2.0 |
| Ethernet Connectivity | RJ-45 Ethernet (10BASE-T/100BASE-TX/1000BASE-T) LAN port Connect with a shielded Ethernet cable (not included); minimum Cat5, or Cat5e or Cat6 for 1000BASE-T. |
| Wi-Fi Connectivity | Protocol: IEEE 802.11 b/g/n Frequency: 2.4 GHz Supported security: WPA/WPA2 |
| USB Connectivity | USB (rev 2.0) B port with a USB A-B cable |
| Sound Emission | Does not exceed 76.5 dB(A) |
| Fuse Sift Control | Interactive touchscreen, physical buttons |
| Included Accessories | Large Brush Small Brush x 2 Pipe Cleaners Dental Picks Gloves Dust Mask Safety Glasses Vacuum Brush Tool Vacuum Crevice Tool Lifting Straps |