

Fiber Blower Comparison



RENT OR LEASE
at www.leaseml.com

RENT OR LEASE
at www.leaseml.com

RENT OR LEASE
at www.leaseml.com

RENT OR LEASE
at www.leaseml.com

	AccelAir 2	Whisper	Breeze	AirStream	JetStream	Tornado
Cable Diameter	.8-3.0mm (.3-.12")	2-8.5mm (.08-.33")	¹ 1-8.5mm (.04-.33")	2.5-11mm (.10-.43")	⁴ 4-20mm (.16-.79")	² 6-32mm (.24-1.26")
Tube Size (O.D.)	3-10mm (.12-.40")	4-18mm (1.5-.63")	4-18mm (1.5-.63")	5-18mm (.20-.71")	12-50mm O.D. (.75-1.50" SDR)	12-63mm O.D. (.75-2.00" SDR)
Flat Drop Compatible	No	Yes	No	Yes	No	No
Cable Speed (Adjustable)	0 - 165 ft/min (0-55m/min) with buckle detection 0 - 328 ft/min (0-100m/min) without buckle detection	0 - 300 ft/min (0 - 90m/min)	0 - 164 ft/min (0-50m/min)	0 - 262 ft/min (0 - 80m/min)	0 - 280 ft/min (0 - 85m/min)	0 - 300 ft/min (0 - 90 m/min)
Max Air Pressure/Volume	220 psi (15 bar) 8.5 cfm (.24m³/min)	220 psi (15 bar) 35 cfm (1m³/min)	220 psi (15 bar) 35 cfm (1m³/min)	220 psi (15 bar) 35 cfm (1m³/min)	³ 220 psi (15 bar) 150-450 cfm (12m³/min)	³ 175 psi (12 bar) 150-450 cfm (4-12m³/min)
Drive	Drive Wheel	Driver Roller	Drive Wheel	Belts	Belts	Belts
Cable Safety	Buckle Protection	Torque Control via Drill	Electronic Torque Control	Torque Control	Hydraulic Pressure Sensing	Hydraulic Pressure Sensing
Power	110/220 VAC or Battery	Varied Speed Drill	110/220 VAC	110/220 VAC	Gas/Hydraulic	Gas/Hydraulic
Length	4.7" (120mm)	9.7" (246mm)	15.3" (390mm)	18.1" (460mm)	24.5" (620mm)	42" (1070mm)
Width	7.2" (184mm)	8.1" (206mm)	10.6" (270mm)	11.8" (300mm)	19" (484mm)	27" (690mm)
Height	6.5" (166mm)	8.5" (216mm)	10" (250mm)	10.6" (270mm)	9.2" (233mm)	48.5" (1230mm)
Weight	6.6 lbs. (3kg)	12 lbs. (5.4kg)	50.6 lbs. (23kg)	33 lbs. (15kg)	68 lbs. (31kg)	155 lbs. (70kg)

¹ 1-2.5mm blown fiber available with add-on kit ² Tube blowing (10 & 12mm O.D.) available with add-on kit ³ Airflow required is duct size dependent ⁴ 4-6mm fiber possible with dedicated