

C30S

- + **Model C30SxS:** Process control with current control
- + **Model C30SxM:** Process control with torque/angle sensor/encoder

Features

- + **Touch panel** (7 Inch - 800 x 600 Pixel)
- + **31 Programmes** (free programme selection using customer interface)
- + **Graphing with adjustable screwdriving strategies**
C30SxM (13 Versions with relative- and pretorque)
C30SxS (11 Versions)
- + **Analysis**
Cycle counter, logfile, pass/fail memory (IO / NIO) and output of prevailing torque, curve export and display via touch panel and WEBER WSK-software for PC
- + **Interfaces**
Customer interface: digital, optional Profibus, ProfiNet, Ethernet IP, DeviceNet, EtherCat
Data interface: USB Stick & PC sockets
- + **Simple integration** with automated assembly systems
- + **Language and units selection**
- + **Optional remote display**
- + **Redundant sensor** (VDA 2862 - class A screw connection)
- + **ESD version available**
- + **Cat. 4 Emergency stop**

Technical data

Torque range [Nm]	up to 200
Depth control	digital or analogue
Measurements [mm]	280 x 225 x 280 (B x T x H)
Weight [kg]	ca. 7.8
Voltage [V/Hz]	230/50 – 60, 115/50 – 60

