

# ARBORIST SUPER 61/64

INSULATED BOOM: VERSALIFT VST-6000-I  
CHASSIS: SKYLIFT MINI-ARBORIST

# SKYLIFT

440-960-2100 | SKYLIFTUS.COM



# ARBORIST SUPER 61/64

INSULATED BOOM: VERSALIFT VST-6000-I  
CHASSIS: SKYLIFT MINI-ARBORIST

# SKYLIFT

440-960-2100 | SKYLIFTUS.COM

## MACHINE SPECIFICATIONS

|                              |   |
|------------------------------|---|
| WEIGHT:                      | 14,500 LBS. (61') / 14,850 LBS. (64')           |
| LENGTH W/ BOOM:              | 24'5" (61') / 24'5" (64')                       |
| CHASSIS LENGTH:              | 13'5"   |
| STOWED HEIGHT:               | 7'7"  |
| WORKING HEIGHT:              | 61' 64' W/ ELEVATOR OPTION                      |
| WIDTH:                       | 35" TRACKS CLOSED – 50" TRACKS OPEN             |
| BASE:                        | HIGH STRENGTH STEEL CONSTRUCTION                |
| DRIVE:                       | TWO SPEED PLANETARY REDUCTION                   |
| TRACKS:                      | 90" RUBBER                                      |
| TRACK ALARMS:                | AUDIBLE ALARM ON RETRACT                        |
| TILT ALARM:                  | DIGITAL & AUDIBLE – SIDE TO SIDE –FRONT TO BACK |
| ENGINE:                      | 25 HP KUBOTA DIESEL - TIER 4 COMPLIANT          |
| FUEL CAPACITY:               | 15 GALLON                                       |
| HYDRAULIC OIL CAPACITY:      | 25 GALLON                                       |
| PUMP:                        | 16 GPM FIXED DISPLACEMENT PISTON PUMP           |
| OPERATING PSI:               | 3,000 PSI                                       |
| UPPER CONTROLS:              | FULL PRESSURE                                   |
| LOWER CONTROLS:              | HYBRID – RADIAL TYPE                            |
| OUTRIGGERS:                  | OUTRIGGER INTERLOCK SYSTEM                      |
| OUTRIGGER SAFETY:            | REAR 18.5' / FRONT 14' / FRONT TO BACK 20.5'    |
| OUTRIGGER SPREAD:            | 7.7 PSI   |
| GROUND PRESSURE:             | STAINLESS LUG ON DECK                           |
| GROUNDING LUG:               |   |
| HYDRAULIC OIL COOLER         |   |
| OPEN CENTER HYDRAULIC SYSTEM |   |
| INSULATION                   | 46KV CATEGORY C PER ANSI 92.2                   |

## BOOM SPECIFICATIONS

|  |   |
|--|---|
| SIDE REACH:                              | 40'   |
| UPPER BOOM INSULATION GAP:               | 38" RETRACTED / 179" EXTENDED               |
| LOWER BOOM INSULATION GAP:               | 24"   |
| BASKET WORK ZONE:                        | UNLIMITED                                   |
| CONTROLS:                                | 3AXIS / 4AXIS SINGLE STICK ISO CONTROL      |
| PLATFORM:                                | FULL PRESSURE ON SIDE OF BOOM               |
| PLATFORM CAPACITY:                       | END-MOUNTED ROTATING 24" X 30" X 42" BUCKET |
| CATEGORY "C" RATING PER ANSI A92.2       | 300 LBS.                                    |
| LOWER CONTROLS ABOVE ROTATION            | CATEGORY "C" RATING PER ANSI A92.2          |
| LOWER CONTROLS OVERRIDE UPPER CONTROLS   | LOWER CONTROLS ABOVE ROTATION               |
| DIELECTRIC ISOLATION SYSTEM FOR PLATFORM | LOWER CONTROLS OVERRIDE UPPER CONTROLS      |

## MACHINE OPTIONS

|   |
|---|
| AUDIBLE ALARM FOR OUTRIGGERS                                      |
| WIRELESS RADIO CONTROL DRIVE                                      |
| HIGH / LOW TWO SPEED THROTTLE                                     |
| EXTRA SET OF PINS FOR ENTIRE MACHINE                              |
| 4 THERMOPLASTIC MOBILE MATS 2' X 8' LONG                          |
| STORAGE BRACKET FOR GROUND MATS ON TRAILER                        |
| ENGINE BLOCK HEATER   |
| PIN ON PAD MOUNT TRANSFORMER CARRIER PLATFORM (1,000 LB CAPACITY) |
| PINTLE EYE EXTENSION ON TRAILER & EXTENDED SAFETY CHAINS          |
| SPARE TRAILER TIRE  |
| BRACKET FOR SPARE TIRE STORAGE ON TRAILER                         |
| ELECTRIC TONGUE JACK  |
| SOLAR BATTERY CHARGER ON TRAILER                                  |
| EXTRA SET OF MACHINE MANUALS                                      |
| 90" NON-MARKING TRACKS  |
| SET OF (4) WOODEN 19.25 x 19.25 x 1-7/8" OUTRIGGER PADS           |
| SET OF (4) PLASTIC 18 x 18 x 1.5" OUTRIGGER PADS                  |

RECOMMENDED TRAILER: 25' / 25,900 LB. G.V.W.R. UTILITY TRAILER

## BOOM OPTIONS

|                                    |
|------------------------------------|
| 2' PLATFORM ELEVATOR               |
| START / STOP AT BASKET             |
| 12V DC EMERGENCY POWER             |
| CONTINUOUS ROTATION                |
| ROTATING PLATFORM                  |
| HYDRAULIC TOOL CIRCUIT AT PLATFORM |