

CHAMP

**SKYLIFT**  
440-960-2100 | SKYLIFTUS.COM



# CHAMP

## MACHINE SPECIFICATIONS

WEIGHT:	3,600 LBS
LENGTH:	OVERALL 8'2"
HEIGHT:	4'8"
WIDTH:	35" TRACKS CLOSED – 50" TRACKS OPEN
BASE:	HIGH-STRENGTH LOW-ALLOY STEEL CONSTRUCTION
DRIVE:	TWO SPEED PLANETARY REDUCTION
CARRIER:	78" RUBBER TRACKS
TRACK ALARMS:	AUDIBLE ALARM ON RETRACT
TILT ALARM:	DIGITAL & AUDIBLE – SIDE TO SIDE – FRONT TO BACK
ENGINE:	24.8 HP KUBOTA DIESEL EPA TIER 4 FINAL COMPLIANT
FUEL CAPACITY:	10 GALLONS
HYDRAULIC OIL CAPACITY:	20 GALLONS
HYDRAULIC OIL COOLER:	YES
HYDRAULIC PUMP:	15 GPM VARIABLE-DISPLACEMENT PISTON
HYDRAULIC TOOL CIRCUIT:	5 GPM @ 2600 RPM / 8 GPM @ 3200 RPM / SET TO CUSTOMER SPEC
OPERATING PSI:	2,000 PSI
CONTROLS:	FULL PRESSURE
AIR COMPRESSOR:	ROTARY-SCREW 60 CFM @3,600 RPM @ 125 PSI
AIR TANK CAPACITY:	19 GALLONS
GENERATOR:	6,000 WATTS @ 3,600 RPM
INVERTER™:	2,400 WATTS @ 2,600-3,600 RPM / 300 WATTS @ 1,800 RPM
NUMBER OF RECEPTACLES:	(1)-220V (2)-120V
AUXILIARY POWER:	(1) - 12 VOLT "CIGARETTE" OUTLET / (2) - USB 5V SOCKETS
WORK LIGHTS:	(2) FRONT-TELESCOPIC (2) REAR-FIXED
TOOLBOX DIMENSIONS:	18" X 18" X 30" ALUMINUM CONSTRUCTION